


GRAVEL CONSTRUCTION BLANKET

N.T.S.

GRAVEL CONSTRUCTION ENTRANCE BLANKET SPECIFICATIONS:


1. STONE SIZE - USE 2" STONE, OR RECLAIMED OR RECYCLED CONCRETE EQUIVALENT.
2. LENGTH - AS REQUIRED, BUT NOT LESS THAN 50 FT.
3. THICKNESS - NOT LESS THAN SIX (6) INCHES.
4. WIDTH - TWELVE (12) FT. MINIMUM, BUT NOT LESS THAN THE FULL WIDTH AT POINTS WHERE INGRESS OR EGRESS OCCURS.
5. FILTER CLOTH - WILL BE PLACED OVER THE ENTIRE AREA PRIOR TO PLACING OF STONE. FILTER WILL NOT BE REQUIRED ON A SINGLE FAMILY LOT.
6. SURFACE WATER - ALL SURFACE WATER FLOWING OR DIVERTED TOWARD CONSTRUCTION ENTRANCES SHALL BE PIPED ACROSS THE ENTRANCE. IF PIPING IS IMPRACTICAL, A MOUNTABLE BERM WITH 5:1 SLOPES WILL BE PERMITTED.
7. MAINTENANCE - THE ENTRANCE SHALL BE MAINTAINED IN A CONDITION WHICH WILL PREVENT TRACKING OR FLOWING OF SEDIMENT ONTO PUBLIC RIGHT-OF-WAY. THIS MAY REQUIRE PERIODIC TOP DRESSING WITH ADDITIONAL STONE AS CONDITIONS DEMAND AND REPAIR AND/OR CLEAN OUT OF ANY MEASURES USED TO TRAP SEDIMENT. ALL SEDIMENT SPILLED, DROPPED, WASHED OR TRACKED ONTO PUBLIC RIGHT-OF-WAY MUST BE REMOVED IMMEDIATELY.
8. WASHING - WHEELS SHALL BE CLEANED TO REMOVE SEDIMENT PRIOR TO ENTRANCE ONTO PUBLIC RIGHT-OF-WAY. WHEN WASHING IS REQUIRED, IT SHALL BE DONE ON A AREA STABILIZED WITH STONE AND WHICH DRAINS INTO A APPROVED SEDIMENT TRAPPING DEVICE.
9. PERIODIC INSPECTION AND NEEDED MAINTENANCE SHALL BE PROVIDED AFTER EACH RAIN.



FOR DUCTILE IRON PIPE DRILL & TAP MAIN AND INSTALL MUELLER CORPORATION STOP H-15008
FOR PVC DRILL MAIN & INSTALL MUELLER H-104 SERVICE SERVICE CLAMP WITH MUELLER CORPORATION STOP H-15028

WATER SERVICE CONNECTION

N.T.S.



DRIVEWAY PAVEMENT SECTION

N.T.S.

7	12/19/17	REVISED FOR PB REVIEW
6	5/21/12	REVISED TO MEET MIXED USE REQUIREMENTS
5	3/17/09	REVISED GARAGE LOCATION
4	12/6/06	REVISED PER PLANNING BOARD COMMENTS OF 10/4/06
3	10/2/06	REVISED PER PLANNING BOARD COMMENTS OF 7/5/06
2	6/30/06	REVISED PER PLANNING BOARD COMMENTS OF 6/21/06
1	6/21/06	FOR PRELIMINARY REVIEW
ISSUE	DATE	DESCRIPTION

SUBDIVISION FOR
DORIAN DEHAAN & JOHN CONDATORE, JR.
SECTION 14, BLOCK 6, LOT 1
TOWN OF CHESTER
ORANGE COUNTY, NEW YORK

GRADING & UTILITIES

LEHMAN & GETZ, P.C.

CONSULTING ENGINEERS
17 RIVER STREET WARWICK, NEW YORK 10990


DAVID A. GETZ, P.E.
N.Y.S. LIC. No. 61265

DRAWN BY: K.H.E.
CHECKED BY: D.G.
JOB No. 1169

DATE: 4/19/06
SCALE: 1" = 20'
SHEET 3 OF 5

NOTES:

1. THE CONTRACTOR SHALL VERIFY THE LOCATION OF ALL EXISTING UTILITY LINES, WHETHER IN THE PUBLIC RIGHT-OF-WAY, IN EASEMENTS, OR IN PRIVATE PROPERTY PRIOR TO STARTING ANY EXCAVATION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE PROTECTION OF ALL UTILITY LINES THROUGHOUT THE COURSE OF CONSTRUCTION. PROJECT SAFETY SHALL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR.
2. ALL NEW UTILITIES SHALL BE CONSTRUCTED UNDERGROUND.
3. CALL BEFORE YOU DIG UNDERGROUND FACILITIES PROTECTIVE ORGANIZATION 2 FULL WORKING DAYS BEFORE YOU DIG AT 1-800-962-7962.



NOTES:

1. WHERE TWO SECTIONS OF FILTER CLOTH ADJOIN EACH OTHER, THEY SHALL BE OVERLAPPED BY SIX INCHES AND FOLDED.
2. MAINTENANCE SHALL BE PERFORMED AS NEEDED AND MATERIAL REMOVED WHEN "BULGES" DEVELOP IN THE SILT FENCE.
3. SILT FENCE FABRIC TO BE MIRAFI 100X OR APPROVED EQUAL.

NO SITE PREPARATION OR CONSTRUCTION, INCLUDING UTILITY CONNECTIONS, SHALL COMMENCE UNTIL A VALID PERMIT HAS BEEN SECURED FROM THE ORANGE COUNTY DEPARTMENT OF PUBLIC WORKS, UNDER SECTION 136 OF THE HIGHWAY LAW.