

**SITE PLAN & SUBDIVISION FOR
1251 KINGS HIGHWAY, LLC**

**TOWN OF CHESTER
ORANGE COUNTY, NEW YORK**

**STORMWATER POLLUTION
PREVENTION PLAN NARRATIVE**

PREPARED FOR:

-1251 KINGS HIGHWAY, LLC
-N.Y.S. DEPARTMENT OF ENVIRONMENTAL CONSERVATION
-THE TOWN OF CHESTER

March 15, 2019

PREPARED BY:

ARDEN CONSULTING ENGINEERS, PLLC
P.O. BOX 340
MONROE, N.Y. 10949
TEL: 845-782-8114
EMAIL: mam@ardenconsulting.net
PROJECT: 18-029

Michael A. Morgante
N.Y.S.P.E. License # 78577



1. INTRODUCTION	4
1.1. Project Description	4
1.2. Existing Drainage Patterns	4
1.3. Proposed Drainage Patterns	5
2. STORMWATER MANAGEMENT.....	5
2.1. General.....	5
2.2. Stormwater Quantity.....	5
2.3. Increase in Stormwater Runoff Rates.....	6
3. STORMWATER QUALITY	7
3.1. Impervious Surfaces	7
3.2. Sources of Pollutants.....	8
3.3. Use of Fertilizers and Pesticides	9
4. PERFORMANCE CRITERIA.....	9
4.1. Infiltration	9
4.1.1. Feasibility.....	9
4.1.2. Conveyance.....	11
4.1.3. Pretreatment.....	11
4.1.4. Treatment	12
4.1.5. Landscaping	13
4.1.6. Maintenance	13
5. EROSION & SEDIMENT CONTROL.....	13
5.1. General.....	13
6. MAINTENANCE OF STORMWATER MANAGEMENT FACILITIES	14
6.1. General.....	14

7. SUMMARY	14
7.1. General.....	14

APPENDICES

APPENDIX A – SOILS MAPPING

**APPENDIX B – SWPPP & BAYFILTER CALCULATIONS, PRE & POST
DEVELOPMENT MAPS, HYDROCAD MODEL, BAYFILTER NJDEP
ACCEPTANCE LETTER**

**APPENDIX C – CONSTRUCTION SITE INSPECTION FORMS (SWPPP &
E&SC)**

APPENDIX D– NOTICE OF INTENT

**APPENDIX E – CONSTRUCTION WASTE MANAGEMENT & SPILL
PREVENTION PLAN**

APPENDIX F – CONTRACTOR CERTIFICATION STATEMENT

1. INTRODUCTION

1.1. Project Description

The site is located near the intersection of Kings Highway and Bellvale Road in the Town of Chester, Orange County, New York. The tax map designation for the parcel is Section 17, Block 1, Lot 99.221. The general land use in the nearby vicinity of the project site is the IP Zoning District, with the AR-3 and SR1 zones also located nearby.

The portion of the site that is proposed for development is characterized by a southeasterly sloping topography that descends from the northern portion of the site. Topography on the site reflects the local surrounding topography. The site was previously used as farm operation for the production of corn.

The soils on the property were identified using the soil classifications of the USDA Soil Conservation Service (SCS), Soil Survey of Orange County, New York and the USGS Soil Survey Database. The site soils consist primarily of the Mardin (MdB) series and the Erie (ErB) series. The Mardin soils consist of moderately well-drained to excessively well drained soils, while Erie soils consist of somewhat poorly drained to very poorly drained soils. The approximate soil boundaries and types are shown on the attached Pre & Post Development Drainage Analysis Maps.

The current proposed project will consist of two separate warehouse units on lot 2 and lot 3 that that are 40,000 SF each. Lot 1 will contain the existing dwelling with no other improvements proposed on this lot. There is an access driveway proposed for each warehouse, with two driveway cuts proposed on Kings Highway and one on Bellvale Road. The warehouse will contain parking, sidewalks, drainage facilities, a drilled well and a subsurface sewage disposal system. The proposed development will disturb more than one acre of soil. Under the requirements of the current SPDES General Permit for Stormwater Discharges from Construction Activity NYS GP-0-15-002, a Stormwater Pollution Prevention Plan (SWPPP) is required.

1.2. Existing Drainage Patterns

Generally, the pre-development site conditions are best described as a mixture of open woods, grass, corn fields, NYSDEC wetlands and impervious surface associated with the existing structures and pavement.

There are two major watersheds within the existing site. The pre-development runoff for Watershed #1 & #2 drains to the NYSDEC wetland located in the southern portion of the property. Runoff collects into a NYSDEC regulated wetland and ultimately leaves the site at the locations noted as Stormwater Design Point 1 & 2 (DP1 & DP2) shown on the attached Pre Development Stormwater Analysis Map.

1.3. Proposed Drainage Patterns

The pre development watershed boundaries are very similar to the post development condition. The proposed warehouse buildings and associated improvements discussed above are located within Watershed #1 & 2. The addition of the impervious surface increases post-developed runoff and pollutants in this watershed. To simplify the analysis for treatment and attenuation of post development stormwater flows, Watershed 1 & 2 was divided into Sub-Watersheds 1A & 1B as well as 2A & 2B, both of which drain into the NYSDEC regulated wetland.

2. STORMWATER MANAGEMENT

2.1. General

In general, increased imperviousness can change the volume and rate of runoff as well as the amount of suspended or dissolved substances entering local streams. In some cases, a change in the amount of impervious surfaces can change the distribution of water in a given area, affecting local water bodies, wetlands and associated fauna and flora. The project design includes measures to reduce the level of runoff and pollutants in post-development runoff in compliance with New York State DEC requirements. This will be achieved by the installation of infiltration facilities and a Bayfilter™ combined with a stormwater basin.

2.2. Stormwater Quantity

The drainage report has been prepared to analyze the impact of stormwater runoff at the major discharge points (DP1 & DP2) on the property. The impact of the proposed development on existing drainage patterns was evaluated for both the pre and post development conditions.

Information and data to prepare this report was obtained from the following sources:

- Topographic, Boundary and Planimetric information from Stephen P. Dolson, NYS L.S.
- Site Plan & Subdivision for 1251 Kings Highway, LLC as prepared by Arden Consulting Engineers, PLLC.
- The site soil information from Orange County Soil Conservation Service & USGS.
- Site evaluations as carried out by personnel from Arden Consulting Engineers, PLLC.

The TR-55 method was used to determine the pre-development and post-development runoff rates at the design points (DP1 & DP2) identified on the property, which is illustrated on the attached drawings entitled Pre Development Stormwater Analysis and Post Development

Stormwater Analysis.

Drainage summaries have been shown on Table 1 & 2, which outline the runoff volume from the 10 and 100 year storm events in the pre-development and post-development conditions, using a Type III storm distribution. The 24 hour rainfall values used for each storm occurrence were taken from the NYSDEC Stormwater Design Manual as listed below:

10 year storm = 4.75 in

100 year storm = 8.5 in

Details of the proposed stormwater facilities have been included on Pre & Post Development Drainage Analysis Maps and the project drawings. The Pre and Post Development Analysis Maps have been prepared to illustrate existing drainage areas and their configuration following construction on the site.

It is the overall goal of the SWPPP to provide for proper drainage control on a quality and quantity basis. The plan has been prepared so there will be no negative effect on downstream properties.

The hydrologic characteristics of the pre-development site conditions were modeled using HydroCad computer software. The model analyzes watershed conditions and provides hydrograph generation and routing based on the Natural Resources Conservation Service (NRCS) Technical Release 55 (TR-55) procedures. These procedures take into account the land cover and use on site, the underlying soils, the general topography and local rainfall distribution to model stormwater runoff volumes and flow rates resulting from the site.

Table 1 below summarizes the pre-development HydroCad modeling results for the design point (DP1) where runoff leaves the site.

Table 1		
Pre-development Runoff to DP1 & DP2		
Storm Frequency	DP1 (cfs)	DP2 (cfs)
10 year	41.80	57.84
100 year	92.16	118.12

2.3. Increase in Stormwater Runoff Rates

The post-development HydroCad modeling results for runoff from the site at the point where runoff reaches Stormwater Design Point 2 (DP2) are shown in Table 2 below.

Table 2		
Post-development Runoff to DP1 & DP2		
Storm Frequency	DP1 (cfs)	DP2 (cfs)
10 year	31.49	57.47
100 year	81.05	109.68

Table 3 below compares the pre- and post-development runoff calculations.

Table 3				
Pre- vs. Post-Development Runoff to DP1 & DP2 (cfs)				
Storm Frequency	DP1 Runoff (Pre)	DP1 Runoff (Post)	DP2 Runoff (Pre)	DP2 Runoff (Post)
10 year	41.80	31.49	57.84	54.47
100 year	92.16	81.05	118.12	109.68

The post-development rates of runoff are less than the existing condition. This requirement meets the standards of the SPDES General Permit for Stormwater Discharges.

3. STORMWATER QUALITY

3.1. Impervious Surfaces

The impervious cover used in this analysis represents the land use as described and shown on the project plans. The supporting calculations for the sizing of the permanent features are presented at the end of this report in Appendix B.

The New York State DEC requires the use of “Unified Stormwater Sizing Criteria” to ensure that water quality, channel erosion reduction, overbank flood protection and safe conveyance of extreme storms is achieved (New York State Stormwater Management Design Manual, January 2015). Water quality volume criteria is based on the following formula:

$$WQ_v = [(P)(R_v)(A)]/12$$

where:

WQ_v = water quality volume (in acre-feet)

P = 90% rainfall event number (in inches)

R_v = 0.05 + 0.009(I), where I is percent impervious cover, and

A = site area in acres

Using this formula for calculating water quality volumes, the following required water quality volumes (WQ_v) were calculated for the watershed. Suitable area and storage volume are provided in the proposed stormwater facilities to meet water quality goals as defined by the

New York State DEC.

Runoff Reduction Volume (RRv) is the reduction of the total WQv by application of green infrastructure techniques and SMPs to replicate pre-development hydrology. The calculations for the RRv can be found in Appendix B. Without the use of stormwater quality management practices, the proposed expansion would result in an increase in the loadings of various chemical constituents to the receiving waters, potentially impairing the quality of those waters within Watershed #1 & #2. A summary has been provided below in Table 4.

TABLE 4
Water Quality Volume (WQv) & Runoff Reduction Volume (RRv) Summary

Watershed	WQv Needed (cf)	RRv Provided (cf)
1A	9,306	9,306
2A	10,120	10,120

An outdoor loading dock area is proposed within both watersheda which qualifies this area as a hot-spot location. The outdoor loading area in Watershed 1 will treat the WQv via the use of a sand filter. The outdoor loading area in Watershed 2 will treat the WQv via the use of an ADS Bayfilter Unit for which supporting calculations can be found in Appendix B. The Bayfilter will discharge into a stormwater basin to provide attenuation of post development stormwater flows. If RRv can be treated elsewhere on the site, then the hotspot area can go directly to a stormwater basin or any other non-infiltration practice. It is proposed to provide RRv for Watershed 2 by the Conservation of Natural Resources practice that consists of the protection of the NYSDEC Wetland and associated buffer.

Runoff from impervious surfaces related to roadways and parking lots poses a potential increase in road and vehicle-related contaminants in the stormwater diverted to treatment facilities. These include hydrocarbons derived primarily from crankcase oil drippings and uncombusted exhaust hydrocarbons. Furthermore, roadway runoff contains detectable levels of heavy and trace metal contaminants such as lead, zinc, copper, chromium and nickel. These types of potential impacts require appropriate mitigation measures to limit impacts to existing water quality.

Stormwater runoff will ultimately discharge as shown on the Post Development Stormwater Analysis Map. The facilities were designed to attenuate and bypass the 10 and 100 year rain event.

3.2. Sources of Pollutants

The New York State DEC lists several potential pollutants and their sources to be considered during site design. Nutrients, sediment, bacteria and various other components can potentially contribute to the reduction of water quality and impacts to downstream receiving waters and habitat for water dependent species.

Many of these constituents, i.e., nitrogen, phosphorus, bacteria and others, are expected to be accounted for in the capture and treatment of the water quality volume. The DEC guidelines have established that if the water quality volume from impervious surfaces is treated, the water quality goals of the State are met. A primary source of nutrients, i.e., the use of fertilizers, is discussed below.

Sediments are typically associated with runoff from unstabilized sites or are the result of erosion in watercourses that cannot handle the velocity of stormwater flows. They can also result from the sanding of impervious surfaces during winter storm events. Unstabilized sediments can be transported via storm flows to receiving wetlands and watercourses, altering the soil-water-air interface in wetlands and burying established vegetation. The current proposal will a sedimentation basin and an infiltration basin that will encourage infiltration of flows carrying unstabilized sediments.

Thermal impacts, i.e., the increase in water temperature caused by the process of water running off of parking lots, roofs and other impervious surfaces that are heated by the sun, are of greatest concern in areas where a site is directly tributary to a Class B creek. There are no Class B creeks near the site from which runoff from these watersheds will drain into. Furthermore, the majority of the site runoff will be treated by means of infiltration. Based on this information, no special consideration was given to moderating the temperature of stormwater leaving the site.

3.3. Use of Fertilizers and Pesticides

The applicant proposes the use of a variety of construction and maintenance techniques reflecting best management practices in order to limit impacts of stormwater runoff. No fertilizers containing phosphorous will be utilized in order to limit pollutants from the project to the maximum extent possible. Use of an infiltration trench with a sediment basin will serve to remove pollutants and attenuate stormwater runoff.

Phosphorus from fertilizer runs off lawns via stormwater and can enter surface waters and ground water, both of which can reach other water bodies. Using phosphorus-free lawn fertilizers is one step that will be taken to protect water quality. The project sponsor therefore proposes that any fertilizers used during construction will be phosphorus-free.

These combined systems have been designed to treat the NYSDEC water quality volume, and control peak flow runoff rates from the 10- and 100-year storm events.

4. PERFORMANCE CRITERIA

The following paragraphs and bullets describe the required performance criteria that have been met for the proposed Stormwater Management Practices (SMP's) as set forth in Chapter 6 of the NYSDEC Stormwater Design Manual (January 2015).

4.1. Infiltration

4.1.1. Feasibility

Required Elements

To be suitable for infiltration, underlying soils shall have an infiltration rate (fc) of at least 0.5 inches per hour, as initially determined from NRCS soil textural classification, and subsequently confirmed by field geotechnical tests (see SWDM Appendix D). The minimum geotechnical testing is one test hole per 5000 sf, with a minimum of two borings per facility (taken within the proposed limits of the facility). Soil testing indicates an acceptable infiltration rate can be achieved for this project.

Soils shall also have a clay content of less than 20% and a silt/clay content of less than 40%. The soil testing that was completed, as shown on the project plans, indicates the on-site soils meet this requirement.

Infiltration practices cannot be located on areas with natural slopes greater than 15%. The natural slope for this project in the proposed area of infiltration is less than 15%.

Infiltration practices cannot be located in fill soils, except the top quarter of an infiltration trench or dry well. The basal area of the infiltration facility is located in native soils. The infiltration facility has been designed to accommodate the 100-year storm and flows from the various storms will discharge into the proposed field inlet located within the infiltration basin.

To protect groundwater from possible contamination, runoff from designated hotspot land uses or activities must not be directed to a formal infiltration facility. In cases where this goal is impossible (e.g., where the storm drain system leads to a large recharge facility designed for flood control), redundant pretreatment must be provided by applying two of the practices listed in Table 5.1 in series, both of which are sized to treat the entire WQv. An ADS Bayfilter™ has been utilized for this project in Watershed 2B.

The bottom of the infiltration facility shall be separated by at least three feet vertically from the seasonally high water table or bedrock layer, as documented by on-site soil testing. (Four feet in sole source aquifers). The average separation to any constraint is a minimum of 3-feet and this project is not located in a sole source aquifer.

Infiltration facilities shall be located at least 100 feet horizontally from any water supply well. Infiltration practices cannot be placed in locations that cause water problems to downgradient properties. Infiltration trenches and basins shall be setback 25 feet downgradient from structures and septic systems. Dry wells shall be separated a minimum of 10 feet from structures. All of these criteria have been met in the design and it does not appear that there are any existing or proposed wells within 100 feet of the infiltration facility.

Design Guidance

The maximum contributing area to infiltration basins or trenches should generally be less than five acres. The infiltration basin can theoretically receive runoff from larger areas, provided that the soil is highly permeable (i.e., greater than 5.0 inches per hour). (See SWDM Appendix L for erosive velocities of grass and soil). Watershed #1C that contributes to the infiltration facility is 1.35 acres and Watershed 2B contributing area is 1.65 acres.

The maximum drainage area to dry wells should generally be smaller than one acre, and should include rooftop runoff only. This is not applicable in this design.

4.1.2. Conveyance

Required Elements

The overland flow path of surface runoff exceeding the capacity of the infiltration system shall be evaluated to preclude erosive concentrated flow during the overbank events. If computed flow velocities exceed erosive velocities (3.5 to 5.0 fps), an overflow channel shall be provided to a stabilized watercourse. The project has been designed such that there are no overbank events even for the 100 year storm.

All infiltration systems shall be designed to fully de-water the entire WQv within 48 hours after the storm event. Based on the soils testing the infiltration basin will de-water within 24-hours.

If runoff is delivered by a storm drain pipe or along the main conveyance system, the infiltration practice must be designed as an off-line practice (see SWDM Appendix K for a detail), except when used as a regional flood control practice. This facility is designed as an on-line practice.

Design Guidance

For infiltration basins and trenches, adequate stormwater outfalls should be provided for the overflow associated with the 10-year design storm event (non-erosive velocities on the down-slope). This has been provided for with overflow catchbasins within the infiltration basin.

For dry wells, all flows that exceed the capacity of the dry well should be passed through the surcharge pipe. This is not applicable to this design.

4.1.3. Pretreatment

Required Elements

A minimum pretreatment volume of 25% of the WQv must be provided prior to entry to an infiltration facility, and can be provided in the form of a sedimentation basin, sump pit, grass channel, plunge pool or other measure.

If the fc for the underlying soils is greater than 2.00 inches per hour, a minimum pretreatment volume of 50% of the WQv must be provided. This is applicable to this project and has been designed for accordingly.

If the fc for the underlying soils is greater than 5.00 inches per hour, 100% of the WQv shall be pretreated prior to entry into an infiltration facility. A sedimentation basin has been included in this design to provide 100% pretreatment and supporting calculations can be found in the Appendices.

Exit velocities from pretreatment chambers shall be non-erosive (3.5 to 5.0 fps) during the two-year design storm. There is a rip-rap overflow berm between the sedimentation basin and the infiltration basin that will result in velocities that are less than 3.5 to 5.0 fps.

Infiltration basins or trenches can have redundant methods to ensure the long-term integrity of the infiltration rate. The following techniques are pretreatment options for infiltration practices:

Grass channel (Maximum velocity of 1 fps for water quality flow. See the Fact Sheet on page 5-10 for more detailed design information.). Not applicable.

Grass filter strip (minimum 20 feet and only if sheet flow is established and maintained).

Bottom sand layer (for I-1). Not applicable.

Upper sand layer (for I-1; 6" minimum with filter fabric at sand/gravel interface). Not applicable.

Use of washed bank run gravel as aggregate. Not applicable.

Alternatively, a pre-treatment settling chamber may be provided and sized to capture the pretreatment volume. Use the method prescribed in section 6.4.3 (i.e., the Camp-Hazen equation) to size the chamber. Not applicable.

A Plunge Pool is not applicable.

An underground trap with a permanent pool between the downspout and the dry well (I-3). Not applicable.

Design Guidance

The sides of infiltration trenches and dry wells should be lined with an acceptable filter fabric that prevents soil piping. Not applicable.

In infiltration trench designs, incorporate a fine gravel or sand layer above the coarse gravel treatment reservoir to serve as a filter layer. Not applicable.

4.1.4. Treatment

Required Elements

Infiltration practices shall be designed to exfiltrate the entire WQv through the floor of each practice (sides are not considered in sizing). This has been designed accordingly.

The construction sequence and specifications for each infiltration practice shall be precisely followed in accordance with this SWPPP report.

Experience has shown that the longevity of infiltration practices is strongly influenced by the care taken during construction.

Design Guidance

Infiltration practices are best used in conjunction with other practices, and downstream detention is often needed to meet the Cp_v and Q_p sizing criteria. This facility will provide Cp_v and Q_p.

A porosity value (V_v/V_t) of 0.4 can be used to design stone reservoirs for infiltration practices. The bottom of the stone reservoir should be completely flat so that infiltrated runoff will be able to infiltrate through the entire surface. Not applicable.

4.1.5. Landscaping

Required Elements

Upstream construction shall be completed and stabilized before connection to a downstream infiltration facility. A dense and vigorous vegetative cover shall be established over the contributing pervious drainage areas before runoff can be accepted into the facility.

Infiltration trenches shall not be constructed until all of the contributing drainage area has been completely stabilized.

Design Guidance

Mow upland and adjacent areas, and seed bare areas.

4.1.6. Maintenance

Required Elements

Infiltration practices shall never serve as a sediment control device during site construction phase. In addition, the Erosion and Sediment Control plan for the site shall clearly indicate how sediment will be prevented from entering an infiltration facility. Normally, the use of diversion berms around the perimeter of the infiltration practice, along with immediate vegetative stabilization and/or mulching can achieve this goal. In this case, the sedimentation basin located upstream of the infiltration basin shall be used as a sediment trap during construction.

An observation well shall be installed in every infiltration trench and dry well, consisting of an anchored six- inch diameter perforated PVC pipe with a lockable cap installed flush with the ground surface. This is not applicable here.

Direct access shall be provided to infiltration practices for maintenance and rehabilitation. If a stone reservoir or perforated pipe is used to temporarily store runoff prior to infiltration, the practice shall not be covered by an impermeable surface. Direct access has been provided.

Design Guidance

OSHA trench safety standards should be consulted if the infiltration trench will be excavated more than five feet. This is not applicable.

Infiltration designs should include dewatering methods in the event of failure. Dewatering can be accomplished with underdrain pipe systems that accommodate drawdown. An underdrain with cleanouts and a valve have been provided.

5. EROSION & SEDIMENT CONTROL

5.1. General

During construction of the Project, extensive erosion and sediment control consisting of vegetative and structural measures will be implemented. These practices will be included in the final plans and will show the location and details of these controls. Among the techniques to be utilized are:

1. Staked haybales and silt fences around the downhill perimeter of the construction.
2. A stabilized construction entrance installed at the access point to the site.
3. Temporary seeding of all disturbed areas if they will remain bare for more than three weeks.
4. Permanent seeding and mulching as soon as possible after final grading.
5. Water spray for dust control.
6. The plans will indicate the proposed controls to be implemented during construction. However, adjustment of these controls may be required to accommodate localized field conditions.
7. Disturbed areas will be permanently stabilized by establishing a permanent vegetative cover. The exposed area will receive a minimum of 4 inch topsoil prior to seeding.

6. MAINTENANCE OF STORMWATER MANAGEMENT FACILITIES

6.1. General

The storm water management facilities shall be maintained by the Owner of the Project during and after construction. All storm water management facilities shall be routinely inspected and any necessary repairs made immediately in order to maintain all practices as designed. The Contractor and Owner shall utilize good housekeeping methods for all litter and debris that is generated during construction. This shall include for example, placing all wastes in a dumpster on a daily basis and emptying dumpsters on a regular basis. It is also recommended to store any chemicals that are utilized during construction in a safe place according to manufacturer's safety data sheets (MSDS).

7. SUMMARY


7.1. General

Drainage from the proposed impervious surfaces will be collected primarily by the infiltration basin. The Soil Conservation Service TR-55 method has been utilized to evaluate the changes in stormwater runoff rates as a result of development of the site. The storm drainage system has been designed to collect and convey stormwater in a manner that would provide no increase in stormwater runoff rates downstream from the property. On-site retention, recharge and filtration via the use of infiltration facilities is necessary and has been provided to mitigate the increases in stormwater runoff rates and pollutants that would otherwise impact downstream conditions.


The proposed project has also been designed to minimize the extent of proposed grading and disturbance. The construction activity on the site will therefore not result in additional pollutant loadings and post development runoff to downstream water bodies. The proposed erosion and sediment practices will prevent the erosion and sediment deposits to downstream properties.

APPENDIX A

Soil Map—Orange County, New York



Soil Map may not be valid at this scale.



Natural Resources
Conservation Service

Web Soil Survey
National Cooperative Soil Survey


3/17/2019
Page 1 of 3


MAP LEGEND

Area of Interest (AOI)

 Area of Interest (AOI)

Soils

 Soil Map Unit Polygons

 Soil Map Unit Lines

 Soil Map Unit Points

Special Point Features



Blowout



Borrow Pit



Clay Spot



Closed Depression



Gravel Pit



Gravelly Spot



Landfill



Lava Flow



Marsh or swamp



Mine or Quarry



Miscellaneous Water



Perennial Water



Rock Outcrop



Saline Spot



Sandy Spot



Severely Eroded Spot



Sinkhole



Slide or Slip



Sodic Spot



Spoil Area



Stony Spot



Very Stony Spot



Wet Spot



Other



Special Line Features

Water Features



Streams and Canals

Transportation



Rails



Interstate Highways



US Routes



Major Roads



Local Roads

Background



Aerial Photography

MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:15,800.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service

Web Soil Survey URL:

Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Orange County, New York

Survey Area Data: Version 19, Sep 3, 2018

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Oct 7, 2013—Feb 26, 2017

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Map Unit Legend

Map Unit Symbol	Map Unit Name	Acres in AOI	Percent of AOI
Ab	Alden silt loam	9.6	22.3%
BnC	Bath-Nassau channery silt loams, 8 to 15 percent slopes	14.3	33.2%
ErB	Erie gravelly silt loam, 3 to 8 percent slopes	0.9	2.0%
Ma	Madalin silt loam	3.2	7.5%
MdB	Mardin gravelly silt loam, 3 to 8 percent slopes	14.5	33.7%
MdD	Mardin gravelly silt loam, 15 to 25 percent slopes	0.6	1.4%
Totals for Area of Interest		43.1	100.0%

APPENDIX B

Is this project subject to Chapter 10 of the NYS Design Manual (i.e. WQv is equal to post-development 1 year runoff volume)?.....

No

Design Point: 1A

P= 1.30

inch

*Manually enter P, Total Area and Impervious Cover.***Breakdown of Subcatchments**

Catchment Number	Total Area (Acres)	Impervious Area (Acres)	Percent Impervious %	Rv	WQv (ft ³)	Description
1	3.44	2.00	58%	0.57	9,306	
2						
3						
4						
5						
6						
7						
8						
9						
10						
Subtotal (1-30)	3.44	2.00	58%	0.57	9,306	Subtotal 1
Total	3.44	2.00	58%	0.57	9,306	Initial WQv

Identify Runoff Reduction Techniques By Area

Technique	Total Contributing Area	Contributing Impervious Area	Notes
	(Acre)	(Acre)	
Conservation of Natural Areas	3.44	2.00	minimum 10,000 sf
Riparian Buffers	0.00	0.00	maximum contributing length 75 feet to 150 feet
Filter Strips	0.00	0.00	
Tree Planting	0.00	0.00	Up to 100 sf directly connected impervious area may be subtracted per tree
Total	3.44	2.00	

Recalculate WQv after application of Area Reduction Techniques

	Total Area (Acres)	Impervious Area (Acres)	Percent Impervious %	Runoff Coefficient Rv	WQv (ft ³)
"<<Initial WQv"	3.44	2.00	58%	0.57	9,306
Subtract Area	-3.44	-2.00			
WQv adjusted after Area Reductions	0.00	0.00	0%	0.05	0
Disconnection of Rooftops		0.00			
Adjusted WQv after Area Reduction and Rooftop Disconnect	0.00	0.00	0%	0.05	0
WQv reduced by Area Reduction techniques					9,306

Conservation of Natural Areas

Design Point:	1A						
Enter Site Data For Drainage Area to be Treated by Practice							
Catchment Number	Total Area (Acres)	Impervious Area (Acres)	Percent Impervious %	Rv	WQv (ft³)	Precipitation (in)	Description
1	3.44	2.00	0.58	0.57	9305.87	1.30	
Design Elements							
Is Contiguous Area \geq 10,000 ft ² ?						Yes	
Will limits of disturbance be clearly shown on all construction drawings and marked in field/project development site with structural barriers?						Yes	
Is the Conservation area located in an acceptable conservation easement instrument that ensures perpetual protection of proposed area?						No	
Does the easement specify how the natural area vegetation will be managed and boundaries will be marked?						No	
Does the conservation area receive runoff from other contributing areas?						No	
Does Conservation Area drain to a Design Point?						No	
Is Sheet Flow to Riparian Buffer or another area based practice already being Used for this area?						No	
Are All Criteria in Section 5.3.1 Met?				Yes			
Area Reduction Adjustments							
Subtract		3.44	Acres from Total Area				
Subtract		2.00	Acres from Total Impervious Area				

Infiltration Basin Worksheet

Design Point:	1A						
Enter Site Data For Drainage Area to be Treated by Practice							
Catchment Number	Total Area (Acres)	Impervious Area (Acres)	Percent Impervious %	Rv	WQv (ft ³)	Precipitation (in)	Description
1	3.44	2.00	0.58	0.57	9305.87	1.30	
Enter Impervious Area Reduced by Disconnection of Rooftops		0.00	58%	0.57	9,306	<<WQv after adjusting for Disconnected Rooftops	
Enter the portion of the WQv that is not reduced for all practices routed to this practice.						ft ³	
Pretreatment Techniques to Prevent Clogging							
Infiltration Rate			5.00	in/hour	Okay		
Pretreatment Sizing			50	% WQv	25% minimum; 50% if >2 in/hr 100% if >5in/hour		
Pretreatment Required Volume			4,653	ft ³			
Pretreatment Provided			4,700	ft ³			
Pretreatment Techniques utilized			Sedimentation Basin				
Size An Infiltration Basin							
Design Volume	9,306	ft ³	WQv				
Basal Area Required	4,653	ft ²	Infiltration practices shall be designed to exfiltrate the entire WQv through the floor of each practice.				
Basal Area Provided	5,000	ft ²					
Design Depth	2.00	ft					
Volume Provided	10,000	ft ³	Storage Volume provided in infiltration basin area (not including pretreatment.				
Determine Runoff Reduction							
RRv	9,000	ft ³	90% of the storage provided in the basin or WQv whichever is smaller				
Volume Treated	306	ft ³	This is the portion of the WQv that is not reduced/infiltrated				
Sizing v	OK		The infiltration basin must provide storage equal to or greater than the WQv of the contributing area.				

Is this project subject to Chapter 10 of the NYS Design Manual (i.e. WQv is equal to post-development 1 year runoff volume)?.....

No

Design Point: 2A

P= 1.30

inch

*Manually enter P, Total Area and Impervious Cover.***Breakdown of Subcatchments**

Catchment Number	Total Area (Acres)	Impervious Area (Acres)	Percent Impervious %	Rv	WQv (ft ³)	Description
1	3.65	2.18	60%	0.59	10,120	
2						
3						
4						
5						
6						
7						
8						
9						
10						
Subtotal (1-30)	3.65	2.18	60%	0.59	10,120	Subtotal 1
Total	3.65	2.18	60%	0.59	10,120	Initial WQv

Identify Runoff Reduction Techniques By Area

Technique	Total Contributing Area	Contributing Impervious Area	Notes
	(Acre)	(Acre)	
Conservation of Natural Areas	3.65	2.18	minimum 10,000 sf
Riparian Buffers	0.00	0.00	maximum contributing length 75 feet to 150 feet
Filter Strips	0.00	0.00	
Tree Planting	0.00	0.00	Up to 100 sf directly connected impervious area may be subtracted per tree
Total	3.65	2.18	

Recalculate WQv after application of Area Reduction Techniques

	Total Area (Acres)	Impervious Area (Acres)	Percent Impervious %	Runoff Coefficient Rv	WQv (ft ³)
"<<Initial WQv"	3.65	2.18	60%	0.59	10,120
Subtract Area	-3.65	-2.18			
WQv adjusted after Area Reductions	0.00	0.00	0%	0.05	0
Disconnection of Rooftops		0.00			
Adjusted WQv after Area Reduction and Rooftop Disconnect	0.00	0.00	0%	0.05	0
WQv reduced by Area Reduction techniques					10,120

Conservation of Natural Areas

Design Point:	2A					
Enter Site Data For Drainage Area to be Treated by Practice						
Catchment Number	Total Area (Acres)	Impervious Area (Acres)	Percent Impervious %	Rv	WQv (ft³)	Precipitation (in)
1	3.65	2.18	0.60	0.59	10119.90	1.30
Design Elements						
Is Contiguous Area $\geq 10,000$ ft ² ?						Yes
Will limits of disturbance be clearly shown on all construction drawings and marked in field/project development site with structural barriers?						Yes
Is the Conservation area located in an acceptable conservation easement instrument that ensures perpetual protection of proposed area?						No
Does the easement specify how the natural area vegetation will be managed and boundaries will be marked?						No
Does the conservation area receive runoff from other contributing areas?						No
Does Conservation Area drain to a Design Point?						No
Is Sheet Flow to Riparian Buffer or another area based practice already being Used for this area?						No
Are All Criteria in Section 5.3.1 Met?						Yes
Area Reduction Adjustments						
Subtract	3.65	Acres from Total Area				
Subtract	2.18	Acres from Total Impervious Area				

BayFilter	
Variables	Flow
P, Annual Rainfall(in)=	48
A (acres)=	1.29
c=	0.95
% Capture=	0.9
TSSIN (mg/L)=	60
QDD(cfs)=	0.700
Exposure (lbs/cart)=	262
Flow per Cartridge (gpm)=	45
VTRT (ft3)=	192178
L (lbs)=	718
Pretreatment	0
TSSIN (mg/L)=	60
L (lbs)=	718
# Cartridges (design)	7
Maintenance Cycle (yrs)=	2.55



State of New Jersey

DEPARTMENT OF ENVIRONMENTAL PROTECTION

Bureau of Nonpoint Pollution Control

Division of Water Quality

Mail Code 401-02B

Post Office Box 420

Trenton, New Jersey 08625-0420

609-633-7021 Fax: 609-777-0432

http://www.state.nj.us/dep/dwq/bnpc_home.htm

CHRIS CHRISTIE
Governor

KIM GUADAGNO
Lt. Governor

BOB MARTIN
Commissioner

December 21, 2017

Daniel J. Figola, PE
General Manager
BaySaver Technologies, LLC
1030 Deer Hollow Drive
Mt. Airy, MD 21771

Re: MTD Laboratory Certification
BayFilter™ Enhanced Media Cartridge by BaySaver Technologies, LLC
Off-line Installation

TSS Removal Rate 80%

Dear Mr. Figola:

This revised certification letter supersedes the Department's prior certification dated January 10, 2017. The revision was completed to add another Enhanced Media Cartridge model (model 530) to the two previously certified EMC models, 545 and 545LP (now relabeled 522).

The Stormwater Management rules under N.J.A.C. 7:8-5.5(b) and 5.7(c) allow the use of manufactured treatment devices (MTDs) for compliance with the design and performance standards at N.J.A.C. 7:8-5 if the pollutant removal rates have been verified by the New Jersey Corporation for Advanced Technology (NJCAT) and have been certified by the New Jersey Department of Environmental Protection (NJDEP). BaySaver Technologies, LLC has requested a Laboratory Certification for the BayFilter™ System.

This project falls under the "Procedure for Obtaining Verification of a Stormwater Manufactured Treatment Device from New Jersey Corporation for Advanced Technology" dated January 25, 2013. The applicable protocol is the "New Jersey Department of Environmental Protection Laboratory Protocol to Assess Total Suspended Solids Removal by a Filtration Manufactured Treatment Device" dated January 25, 2013.

NJCAT verification documents submitted to the NJDEP indicate that the requirements of the aforementioned protocol have been met or exceeded. The NJCAT letter also included a recommended certification TSS removal rate and the required maintenance plan. The NJCAT Verification Report with

the Verification Appendix for this device is published online at <http://www.njcat.org/verification-process/technology-verification-database.html>.

The NJDEP certifies the use of the BayFilter™ by BaySaver Technologies, LLC at a TSS removal rate of 80%, when designed, operated and maintained in accordance with the information provided in the Verification Appendix and subject to the following conditions:

1. The maximum treatment flow rate (MTFR) for the manufactured treatment device (MTD) is calculated using the New Jersey Water Quality Design Storm (1.25 inches in 2 hrs.) in N.J.A.C. 7:8-5.5. The MTFR is calculated based on a verified loading rate of 0.5 gpm/sf of effective filtration treatment area for models 545 and 522, and 0.33 gpm/sq.ft. for model 530.
2. The BayFilter™ System shall be installed using the same configuration as the unit verified by NJCAT, and sized in accordance with the criteria specified in item 6 below.
3. This device cannot be used in series with another MTD or a media filter (such as a sand filter), to achieve an enhanced removal rate for total suspended solids (TSS) removal under N.J.A.C. 7:8-5.5.
4. Additional design criteria for MTDs can be found in Chapter 9.6 of the New Jersey Stormwater Best Management Practices (NJ Stormwater BMP) Manual which can be found on-line at www.njstormwater.org.
5. The maintenance plan for a site using this device shall incorporate, at a minimum, the maintenance requirements for the BayFilter™, which is attached to this document. However, it is recommended to review the maintenance website at <http://www.baysaver.com/downloads/BayFilter-Technical-and-Design-Manual.pdf> for any changes to the maintenance requirements.
6. Sizing Requirements:

The example below demonstrates the sizing procedure for a BayFilter™ System.

Example: A 0.25-acre impervious site is to be treated to 80% TSS removal using a BayFilter™ System. The impervious site runoff (Q) based on the New Jersey Water Quality Design Storm was determined to be 0.79 cfs or 354.58 gpm.

The selection of configuration for use in the BayFilter™ System is based upon both the MTFR and the maximum inflow drainage area. It is necessary to select the configuration using both methods and to rely on the method that results in the larger configuration determined by the two methods.

Inflow Drainage Area Evaluation:

The drainage area to the BayFilter™ System in this example is 0.25 acres. Based upon the information in Table 1 below, the following minimum configurations are required in a

BayFilter™ System to treat the impervious area without exceeding the maximum drainage area:

1. BayFilter™ 545 EMC: Configuration 4' manhole
2. BayFilter™ 530 EMC: Configuration 4' manhole
3. BayFilter™ 522 EMC: Configuration 4' by 6' vault

Maximum Treatment Flow Rate (MTFR) Evaluation:

The site runoff (Q) was determined based on the following:

time of concentration = 10 minutes

i=3.2 in/hr. (page 5-8, Fig. 5-3 of the NJ Stormwater BMP Manual)

c=0.99 (runoff coefficient for impervious)

$Q=ciA=0.99 \times 3.2 \times 0.25 = 0.79$ cfs = 0.79×448.83 gpm = 354.58 gpm

Based on a flow rate of 354.58 gpm, the following minimum configurations are required in a BayFilter™ System to treat the impervious area without exceeding the MTFR:

1. BayFilter™ 545 EMC: Configuration 8' by 10' vault
2. BayFilter™ 530 EMC: Configuration 8' by 12' vault
3. BayFilter™ 522 EMC: Configuration 8' by 16' vault

The MTFR Evaluation results will be used since that method results in the higher minimum configuration determined by the two methods.

The sizing table corresponding to the available system models are noted below. Additional specifications regarding each model can be found in the Verification Appendix under Table A-1 and Table A-2.

Table 1 BayFilter™ Models

Configuration	MTFR ¹ (gpm)			Maximum Allowable Drainage Area ² (acres)		
	545	530	522	545	530	522
4' manhole	45	30	22.5	0.44	0.44	0.22
4' by 6' vault	90	60	45	0.87	0.87	0.44
5' manhole	135	90	67.5	1.31	1.31	0.66
6' manhole	180	120	90	1.75	1.75	0.87
6' by 6' vault	180	120	90	1.75	1.75	0.87
7' manhole	225	150	112.5	2.18	2.18	1.09
8' manhole	315	210	157.5	3.06	3.06	1.53
8' by 10' vault	450	300	225	4.37	4.37	2.18

8' by 12' vault	585	390	292.5	5.68	5.68	2.84
8' by 14' vault	675	450	337.5	6.55	6.55	3.28
8' by 16' vault	810	540	405	7.86	7.86	3.93
10' by 16' vault	945	630	472.5	9.17	9.17	4.59
10' by 20' vault	1215	810	607.5	11.79	11.79	5.90
<ol style="list-style-type: none"> 1. Based on 0.5 gpm/sq. ft. of effective filtration treatment area for 545 and 522. 0.33 gpm/sq.ft. for 530. 2. Based on the equation in the NJDEP Filter Protocol: Maximum Inflow Drainage Area (acres) = Weight of TSS before 10% loss in MTFR (lbs.)/600 lbs. per acre of drainage area annually. 						

Be advised a detailed maintenance plan is mandatory for any project with a Stormwater BMP subject to the Stormwater Management Rules, N.J.A.C. 7:8. The plan must include all of the items identified in Stormwater Management Rules, N.J.A.C. 7:8-5.8. Such items include, but are not limited to, the list of indication of problems in the system, and training of maintenance personnel. Additional information can be found in Chapter 8: Maintenance and Retrofit of Stormwater Management Measures.

If you have any questions regarding the above information, please contact Shashi Nayak of my office at (609) 633-7021.

Sincerely,



James J. Murphy, Chief
Bureau of Nonpoint Pollution Control

Attachment: Maintenance Plan

cc: Chron File
Richard Magee, NJCAT
Vince Mazzei, NJDEP - DLUR
Ravi Patraju, NJDEP - BES
Gabriel Mahon, NJDEP - BNPC
Shashi Nayak, NJDEP – BNPC



BayFilter

Technical and Design Manual



www.BaySaver.com

BAYFILTER™ SYSTEM

Technical and Design Manual

© BaySaver Technologies, Inc.
1302 Rising Ridge Road, Unit One
Mount Airy, Maryland 21771
Phone 301-829-6470 • Fax 301-829-3747

Table of Contents

INTRODUCTION	1
---------------------------	----------

PRINCIPLES OF OPERATION .	2
----------------------------------	----------

Media Filtration	2
------------------------	---

Mechanisms of Removal.....	2
----------------------------	---

The BayFilter™ Cartridge.....	2
-------------------------------	---

The Drain Down Module.....	4
----------------------------	---

Performance Characteristics	4
-----------------------------------	---

DESIGN GUIDELINES FOR THE BAYFILTER™ SYSTEM	6
--	----------

BayFilter™ Treatment Train Design	6
On-line and Off-line Systems	6
Pretreatment	7
Extended Detention Systems	8

Selecting the Number of Cartridges	9
Required Data	9
Flow Capacity	10
Sediment Load Capacity	10
Water Quality Volume.....	12

Determining the Size of the Flow Restrictor Disk	13
--	----

Determining the Number of Drain Down Modules.....	14
---	----

Preparing Site Plans for the BayFilter™ System	14
Location	14
Standard Details and Notes.....	14

BayFilter™ System Configuration	14
Manhole BayFilter™	15
Precast Vault BayFilter™	16
Box Culvert BayFilter™	17

Cast-in-place BayFilter™	18
--------------------------------	----

INSTALLATION OF THE BAYFILTER™ SYSTEM	19
--	-----------

Tool List	20
-----------------	----

Trolley Installation Instructions	21
---	----

MAINTENANCE OF THE BAYFILTER™ SYSTEM	22
---	-----------

Maintenance Procedures	23
------------------------------	----

BAYFILTER™ SYSTEM COSTS AND AVAILABILITY	24
---	-----------

BAYFILTER™ DETAILED OPERATING SEQUENCE	25
---	-----------

SYSTEM DRAWINGS.....	31
-----------------------------	-----------

PROJECT INFORMATION SHEET	53
--	-----------

Introduction

Founded in 1997, BaySaver Technologies, Inc. is a manufacturer of stormwater treatment technologies. BayFilter™⁽¹⁾ is a stormwater filtration device designed to remove fine sediments, heavy metals, and phosphorus from stormwater runoff.

BayFilter™ relies on a spiral wound media filter cartridge with approximately 43 square feet of active filtration area. The filter cartridges are housed in a concrete structure that evenly distributes the flow between cartridges. System design is offline with an external bypass that routes high intensity storms away from the system to prevent sediment resuspension. Flow through the filter cartridges is gravity driven and self-regulating, which makes the BayFilter™ system a low maintenance, high performance stormwater treatment technology.

The BayFilter™ system has been extensively tested, and has consistently shown more than 80% removal of suspended sediment from influent water. The system also demonstrated the capability to remove more than 50% of the total phosphorus influent load, including a portion of the dissolved phosphorus.

This manual provides detailed technical information on the BayFilter™ system including its capabilities and limitations. The manual describes the steps involved in designing a BayFilter™ system as well as the installation and maintenance requirements of the system.

BaySaver Technologies is a complete stormwater solutions provider. We are always willing to assist design professionals to achieve the most efficient, economical systems for their clients and projects. Please call the BaySaver Technologies Inc. Engineering Department at 1.800.229.7283 for assistance.

⁽¹⁾ The BayFilter™ stormwater filtration system is protected by U.S. Patent #6869528, in addition to several pending patents.

Principles of Operation

The BayFilter™ system removes contaminants from stormwater runoff via media filtration. This Technical and Design Manual describes the principles by which the BayFilter™ system works to improve the quality of the environment throughout the United States.

Media Filtration

Media filtration has long been used in drinking water and wastewater treatment processes. This technology has proven effective at removing sediments, nutrients, heavy metals, and a wide variety of organic contaminants. The target pollutants, hydraulic retention time, filter media, pretreatment, and flow rate all affect the removal efficiency of the filter.


Mechanisms of Removal

The BayFilter™ removes pollutants from water by two mechanisms: 1) interception/attachment and 2) adsorption. Interception occurs when a pollutant becomes trapped within the filter media. A sediment particle, for example, may be carried into the filter media by the water and become stuck in the interstices of the media. Such a particle will typically remain trapped within the media until the media is removed or the filter is backwashed.

Attachment occurs when pollutants bind themselves to the surface of the filter media, and this happens primarily through adsorption. Adsorption is a surface process by which dissolved ions are removed from a solution and chemically bind themselves to the surface of the media. This occurs when the surface of the filter media particle contains sites that are chemically attractive to the dissolved ions. The BayFilter™ system uses a proprietary media containing activated alumina to enhance adsorption of anions such as phosphates.

The BayFilter™ Cartridge

The main building block of the BayFilter™ stormwater filtration system is the BayFilter™ cartridge (BFC), shown in Figure 1. The BFCs are housed in a structure which may be a vault, manhole or other structure. This structure contains the inlet and outlet pipes as well as an internal manifold that delivers treated water to the outlet of the BayFilter™ system.




Stormwater runoff enters the manhole or concrete structure via an inlet pipe and begins to fill the structure. When the water surface elevation in the vault/manhole reaches operating level, water flows through the BFC driven by a hydrostatic head. Within the BFC, the water flows through a proprietary filter media and drains via a vertical pipe. The vertical drain is connected to the under drain system which conveys filtered water to the outfall.

During a typical storm event, the BayFilter™ system has four cycles:

1. Vault fill and air release;
2. Uniform bed load hydrodynamic filtration;
3. Uniform bed load siphon filtration; and

4. Siphon break and hydrodynamic backwash.

**Figure 2:** Drain Down Module

A detailed depiction of the BFC operating sequence is given in Appendix A.

The Drain Down Module

Each BayFilter™ Stormwater Treatment System will include a number of standard BFCs and at least one drain down module per BFC. The drain down module which has a flow capacity of 0.5 gpm, will allow the manhole/vault to empty after the siphon has broken and the standard BFCs are no longer operating. The drain down module prevents the system from retaining standing water between storm events, thereby reducing the chance of mosquitoes or other disease vectors breeding within the system and preventing the system from becoming anaerobic during dry periods. This cartridge also uses the same media as the BFC and has a removal efficiency in excess of 90 percent.

Performance Characteristics

The BayFilter™ has been extensively tested in the laboratory. This testing has been carried out using SIL-CO-SIL 106 as a sediment source. SIL-CO-SIL

106 is a silica product containing approximately 90% fine sediments ($d_{50} = 23$ microns), and is widely accepted as a sediment source for stormwater simulations by regulatory agencies such as the Washington State Department of Ecology (TAPE) program, New Jersey Department of Environmental Protection (TARP), as well as other leading agencies.

The BFC needs only 28" of depth of water to begin full flow operation. Once the full flow operation has been achieved, the BFC will operate to a depth of 6" at which time the siphon will break and the system will backwash. At this point the only flow is from the drain down cartridge which will drain the vault to a depth below 1".

Each BFC has a maximum nominal flow of 30 gpm. At this flow, each cartridge can treat 150 lbs of the total sediment load before maintenance. In addition, through the use of different size flow control orifice(s), the BFC flow is regulated. As the flow is lowered, the treated sediment load increases. For example, when the flow is lowered to 15 gpm, the cartridge is able to treat 300 lbs of the total sediment load before maintenance.

Design Guidelines for the BayFilter™ System

Designing a BayFilter™ system is done in four phases: (1) determine the treatment train design; (2) locate the system on the site and incorporate it into the plans; (3) determine the number of cartridges, size of the flow restrictor disks and number of drain down modules necessary; and (4) select a system configuration. It is important to realize that the design process can be iterative until the desired design parameters are satisfied. Again, it is important to note that the BayFilter™ systems are designed offline. This section details the design process and provides examples for each of the three steps. During the design process, the engineer must consider factors in addition to regulatory requirements. These include:

- Site specific constraints
- Proposed system location
- System configuration (flow through or extended detention)
- Pretreatment
- Efficiency requirements
- Pollutant loading (sediment load)
- Treatment flow rates and hydraulics
- Maintenance intervals


BayFilter™ Treatment Train Design

On-line and Off-line Systems

BayFilter™ systems are usually designed to treat moderate to low flow rates. In the vast majority of applications, the peak design flow through the storm

drain system will be significantly greater than the treatment design flow through BayFilter™. Because of this difference, a bypass structure is required for most BayFilter™ installations. Therefore, BayFilter™ systems are installed offline, utilizing an external bypass to route high flows around the system.

A schematic of an offline BayFilter™ system is shown in Figure 3 below. The bypass structure diverts low flows to the BayFilter™ system and allows high flows to pass to a separate outfall. The bypass structure will feature flow controls designed by an engineer to ensure that the required treatment flows are sent to the BayFilter™. The two effluent streams (the treated effluent from the BayFilter™ and the high intensity bypass) may be combined into a single stream or discharged to separate outfalls. These configurations typically involve higher flow per cartridge, but reduced treated sediment load per cartridge. These configurations are, however, usually limited more by flow sediment capacity.



In BayFilter™ installations sediment will accumulate in the vault as well as in the filter cartridges. In offline installations high intensity flows are routed away from the vault minimizing the risk of resuspending this accumulated sediment. In online applications it is possible for high flows to mobilize and release this sediment.


Pretreatment

The BayFilter™ system is designed to remove a minimum of 80% of suspended sediments and 50% of the total phosphorus load. If the anticipated sediment load is particularly heavy or if there will be a significant oil load, the system may require pretreatment.

Pretreatment may also be required by local regulations. Pretreatment systems will remove a portion of the influent pollutant load. BaySaver


Technologies, Inc. BaySeparator™ system is an ideal hydrodynamic separator that removes sediments and floatables from stormwater runoff.

Figure 4 shows a schematic of a typical BayFilter™ installation with pretreatment. Note that the pretreatment structure is downstream from the bypass. The system will work as long as 28" of head is achieved to activate the cartridge flow and will continue to work until it reaches the siphon break level (6"). Consult BaySaver Technologies, Inc. Engineering Department for verification based on your particular site conditions.



Extended Detention Systems

In some applications, BayFilter™ systems will be installed in conjunction with extended detention systems. Extended detention systems attenuate peak flow rates within the storm drain system. In these cases, the BayFilter™ is placed downstream from an extended detention system, as shown in Figure 5.



Systems with smaller drops can be designed as well. The system will work as long as 28" of head is achieved to activate the cartridge flow and will continue to work until it reaches the siphon break level (6"). Consult BaySaver Technologies, Inc. Engineering Department for verification based on your particular site conditions.

Selecting the Number of Cartridges

Each BayFilter™ system relies on a collection of individual cartridges to achieve the desired removal efficiency and it is important to correctly determine the number of filter cartridges required. Too few cartridges will result in a system that does not meet the performance specifications while too many cartridges will result in a system larger than necessary for the site.

To accurately determine the number of cartridges required for a BayFilter™ installation, three factors must be considered:

- **The flow capacity of the system**
- **Treated sediment load of the system**
- **Jurisdiction – specific sizing requirements (water quality volume)**

Each of the above factors when evaluated will determine a minimum of cartridges required to address that design parameter. Calculations for all three factors need to be done to determine which design parameter is the limiting factor. In each case it will be the computation that results in the highest minimum number of cartridges, the one that will determine the cartridge count. In other words, whichever item requires the most cartridges to meet any one particular design parameter will determine the minimum number of cartridges required for the system.

Required Data

To ensure that the correct number of cartridges is specified for the BayFilter™ system, the designer must be aware of the local regulatory requirements for stormwater treatment. Depending on the jurisdiction in which the project site is located, the engineer may have to meet minimum treatment flow rates, treatment volumes or some other criteria such as filter bed area. Some jurisdictions specify a methodology for calculating a minimum treatment flow rate for a given site. Other jurisdictions may require extended detention upstream from the filtration system or have volume-based rather than flow-based requirements.

Flow Capacity

At many sites regulatory requirements will specify a minimum treatment flow rate (Q_{TRT}) that must be passed through the stormwater treatment system. These regulatory requirements may also specify pretreatment or extended detention practices that need to be included in the site design. Some jurisdictions specify that the stormwater filtration systems be designed on the basis of filter area following prescribed methodologies.

In most cases pretreatment can be provided by a hydrodynamic separator like the BaySaver Technologies, Inc. BaySeparator™ system. Regardless of the pretreatment design, the minimum number of BayFilter™ cartridges can be determined by dividing the treatment flow rate by 30 gpm (0.067 cfs) and rounding up to the next whole number using Equation 1. This calculation provides the minimum number of BFCs that will be necessary to fully treat the water quality flow from the site. This computation does not take into account the sediment load portion of the design, which needs to be performed as well. The design flow per cartridge will ultimately be determined by the cartridge sediment load (Table 1). The step-by-step procedure is shown below.

1. Determine the required treatment flow rate (Q_{TRT}) based on locally approved methodologies for the project site. This may involve the use of the Rational Method, TR-55 or another locally specified hydrologic model. If a locally approved methodology is not specified, BaySaver Technologies, Inc. recommends using one of these commonly accepted models.
2. Using the treatment flow rate, calculate the minimum numbers of BayFilter™ cartridges required to treat that flow using Equation 1.

$$\#Cartridges = \frac{Q_{TRT}(cfs) * 448.8 \frac{gpm}{cfs}}{Q_{BFC}} \quad \text{Equation 1}$$

The minimum number of BFCs is equal to the maximum treatment flow rate divided by Q_{BFC} , rounded up to the next whole number. In most cases, Q_{BFC} will be 30 gpm (0.067 cfs) per cartridge.

Sediment Load Capacity

Once the minimum number of BFCs required to treat the flow is known, the engineer must ensure that the number of BFCs specified will be capable of handling the sediment load from the site. BayFilter™ systems are typically designed around a maintenance cycle. It is important to note that the number of BFCs required to treat the anticipated total system sediment load is a minimum

number. For any site, it is necessary to calculate the minimum number of BFCs required to treat both the peak flow rate and the total system sediment load (as discussed in this section). The number of BFCs required for the site is the greater of the calculated numbers.

To ensure that the BayFilter™ will function acceptably with annual maintenance, it is necessary to calculate the incoming annual sediment load from the site.

1. Calculate the annual treated runoff volume according to Equation 2. In Equation 3, V_{TRT} is the annual treated runoff volume, P is the

$$V_{TRT} (ft^3) = P * A * c * \frac{1ft}{12in} * \frac{43560 ft^2}{acre} * \% Capture$$

Equation 2

average annual precipitation (in inches), A is the area of the site (in acres), c is the runoff coefficient of the site (c is dimensionless), and $\% Capture$ is the fraction of the total runoff that is treated by the stormwater quality system. If $\% Capture$ is not otherwise specified, a default value of 0.90 can be used.

2. Using the annual treated runoff volume, calculate the anticipated total system sediment load to BayFilter™ according to Equation 3. In Equation 3, L is the mass of sediment that BayFilter™ is exposed to annually (in pounds), V_{TRT} is the annual treated runoff volume as calculated in step 1 (in ft^3), and TSS_{IN} is the influent concentration of TSS in the runoff (in mg/L). The influent TSS concentration (TSS_{IN})

$$L = V_{TRT} * TSS_{IN} * \frac{28.3L}{ft^3} * \frac{kg}{10^6 mg} * \frac{2.2lbs}{kg}$$

Equation 3

depends greatly on the site and the surrounding land use. In the absence of readily available data, BaySaver Technologies, Inc. recommends using a minimum event mean concentration (EMC) TSS value of 60 mg/l . The impact of the on the filter cartridge will also be less if the filtration system is preceded by pretreatment. In these cases, the influent TSS to the BayFilter™ system need to be reduced to reflect pretreatment sediment removal. The BaySaver Technologies' Engineering Department can assist with these calculations.

3. Once the total annual system sediment load (L) is calculated, the engineer must ensure that the number of cartridges specified will be able to remove that sediment load at the specified design flow rate. Divide the total system sediment load L by the capacity of each BFC and note the associated BFC flow rate. Round up to the next whole number to get the minimum number of BFCs required to treat this sediment load at the required flow rate per BFC.

Water Quality Volume

In some cases the BayFilter™ system will have to be placed downstream from an extended detention facility or local regulations will specify a treatment volume rather than a treatment flow rate. In these cases the minimum number of BFCs may not be determined using the treatment flow rate calculation. Instead, the minimum number of cartridges for this system depends on the controlled discharge rate Q_{TRT} from the upstream detention facility or the filtration system.

1. Determine the WQv for the site. This may vary significantly from one jurisdiction to the next based on local regulations. Maryland for instance requires that new developments treat the first one inch of water coming off of the site.
2. Most jurisdictions will also specify a drain down time for the detention system. This is usually in the 24 to 40 hour range. It is recommended that the maximum drain down time not exceed 40 hours, beyond which the detained water could potentially become anoxic. BayFilter systems should instead be designed with an initial drain down time of less than 40 hours. Then, as the filter cartridges become occluded, the drain down time will gradually increase to 40 hours. Once it takes in excess of 40 hours for the detention system to fully drain out then the BayFilter system should be maintained.
3. Once you have determined the WQv and the drain down time, the quantity of BayFilter cartridges can be determined by dividing the WQv by the drain down time and then dividing the resulting number by the treatment flow rate of a BayFilter cartridge. For volume based BayFilter systems, the treatment flow rate of each cartridge should be limited to 15 gpm. For example if:

$$WQv = 10,000cf$$

$$\text{Drain down time} = 24\text{hrs (1440min)}$$

$$\text{BFC flow rate} = 15\text{gpm}$$

$$\text{Number of BFC's} = ((10,000cf/86,400)*448.83)/15\text{gpm}$$

$$\text{Number of BFC's} = 4$$

Determine the Size of the Flow Restrictor Disk:

The BayFilter cartridges have a flow restrictor disk that controls the initial filtration rate of the cartridge until the media within the cartridge becomes partially filled with solids; at which time the media becomes the flow restriction and the flow restrictor disk is rendered moot. The flow restrictor is initially sized to restrict the WQv release to 24 hours. Over time as the filters become partially restricted this will exceed the 24 hours. When the BayFilter Cartridges no longer release the WQv within 40 hours, the cartridges must be maintained.

1. Continuing from our previous example, if the desired drain down time is 24 hours and the site requires 4 BayFilter Cartridges, then the actual per cartridge flow rate is calculated by:

Per Cartridge Flow Rate (gpm) = $((WQv/86,400) * 448.83)/\# \text{ of BFC's}$

Per Cartridge Flow Rate (gpm) = $(10,000cf/86400) * 448.83/4$

Per Cartridge Flow Rate (gpm) = 13gpm

2. From this, the orifice size can be determined based on the chart below:

BFC Cartridge Flow in (GPM)

Head	Orifice Diameter (Inches)							
(ft)	1.32"	1.24"	1.14"	0.80"	0.75"	0.70"	0.60"	0.50"
5				13.5	11.6	9.9	6.6	4.4
4.8				12.9	11.1	9.4	6.4	4.3
4.6			30.3	12.4	10.7	9.0	6.2	4.2
4.4			29.6	12.1	10.4	8.7	6.1	4.1
4.2			29.2	11.5	9.9	8.3	5.9	4.0
4.0			26.1	10.8	9.4	8.1	5.8	3.9
3.8			22.8	10.2	8.8	7.4	5.6	3.8
3.5			19.4	9.7	8.3	7.1	5.5	3.7
3.3			18.4	9.3	8.0	6.7	5.3	3.6
3.1		30.4	17.7	8.8	7.6	6.4	5.1	3.5
3.0		24.3	15.7	8.3	7.1	6.0	5.0	3.3
2.7		22.4	14.0	8.0	6.9	5.8	4.8	3.2
2.5*	30.5	20.5	12.4	7.7	6.7	5.6	4.6	3.1

* Note when the head is below 2.5 it continues to function at the equivalent head of 2.5 because the system goes into siphon.

Determining the Number of Drain Down Modules (DDM's):

The number of drain down modules is almost always equal to the number of BayFilter cartridges. Their purpose is to remove any excess standing water from the BayFilter vault once the siphon has broken. Therefore, in rare instances it may be beneficial to add additional drain down modules to a system if very high influent sediment loads are expected.

Preparing Site Plans for the BayFilter™ System

Once the BayFilter™ system has been selected, the chosen system must be included on the site plans.

Location

The location of BayFilter™ on the site will be determined by several factors; maintenance access, the unit's footprint, available drop, available depth, and the surface elevation of the receiving waters must all be considered when selecting the system's location. The location and configuration must be in compliance with MCDPS's underground SWM Structure regulations

The BayFilter™ system must be installed in an area that is accessible to maintenance equipment. The maintenance of a BayFilter™ system requires a vacuum truck as well as the removal and replacement of the filter cartridges. The manhole covers, and or Access Hatches of the BayFilter™ must be placed in locations that can be easily reached by such a vehicle.

The BayFilter™ should be placed in a location that minimizes its interference with other existing or planned underground utilities.

Standard Details and Notes


All of the standard details and notes for the plans are available in AutoCAD and .pdf format from BaySaver Technologies, Inc. They are also be available on the Website at www.BaySaver.com

BayFilter System Configuration

There are four (4) types of BayFilter systems:

- 1.) Manhole: Standard precast manholes with O-Ring gasket joints
- 2.) Precast vault: Monolithically poured concrete vault (base and walls)
- 3.) Box culvert vault: Must be made by MCDPS approved supplier
- 4.) Cast in place vault: Custom designed for site.

Manhole BayFilter™




Manhole BayFilter™ systems have a small footprint, and can be fit into site plans easily without interfering with other underground utilities. Manhole BayFilter™ systems are ideal for applications downstream from water quality detention structures. Please consult with the BaySaver Technologies, Inc. Engineering Department for more details.

Access to the Manhole BayFilter™ for inspection or maintenance is achieved through a minimum 30" diameter frame and cover. In each Manhole BayFilter™ system, the BFCs are arranged so that a maintenance worker can stand on the floor of the manhole while installing or removing the cartridges. Please refer to Appendix C for engineering drawings showing the available Manhole BayFilter™ configurations.

Available manhole filter systems include:

BayFilter™ Model	Manhole Size	Maximum Number of BFCs	Maximum Treatment Flow gpm (cfs)
MHF-60-3	60"	3	90 (0.20)
MHF-72-4	72"	4	120 (0.27)
MHF-84-5	84"	5	150 (0.33)
MHF-96-7	96"	7	210 (0.47)

Precast Vault BayFilter™

When more BFCs are required, Precast Vault BayFilter™ systems may be used on larger sites or sites with more impervious area. The Precast Vault BayFilter™ system is larger than the Manhole BayFilter™. Constructed within a precast concrete vault, it has a treatment capacity ranging from 240 gpm (0.53 cfs) in an 8' x 10' vault to 2,010 gpm (4.48 cfs) in a 10' x 48' vault. Should precast vaults of the dimensions outlined not be available locally, these structures can be cast in place. The table below shows the available Precast Vault BayFilter™ systems, along with the maximum number of filter cartridges and treatment capacities. The minimum system drop is typically 28" however this can be

reduced on a site specific basis by BaySaver Technologies, Inc. in conjunction with an engineer.

The figure above shows the layout of a PVF-8-10-10, an 8' x 10' precast vault BayFilter™ system. The system comprises ten standard BFCs and 10 drain down modules. Unlike the manhole BayFilter™, the outlet manifold in the precast vault BayFilter™ does not connect directly to the outlet pipe. Instead, each of the under drain lines enters an outlet manifold which drains to the outlet pipe.

Box Culvert BayFilter™

Like the manhole BayFilter™, access to the box culvert BayFilter™ is provided through the hinged access hatch. The box culvert BayFilter™ is constructed in 10' x 6' sections. Each vault has at least one access hatch. The BFCs and outlet manifolds are arranged to allow maintenance personnel to stand on the concrete floor while working inside the structure. The BayFilter™ cartridges and under drain manifold components are supplied by BaySaver Technologies, Inc. together with the precast vaults. Please refer to Appendix C for a complete set of box culvert BayFilter™ configurations.

Available precast vault and box culvert filter systems include:

BayFilter™ Model	Vault Size (ft x ft)	Maximum Number of BFCs	Maximum Treatment Flow gpm (cfs)
PVF-8-10-10	8' x 10'	10	300 (0.67)
PVF-8-12-13	8' x 12'	13	390 (0.87)
PVF-8-14-15	8' x 14'	15	450 (1.00)
PVF-8-16-18	8' x 16'	18	540 (1.20)
PVF-10-16-21	10' x 16'	21	630 (1.40)
PVF-10-20-27	10 x 20'	27	810 (1.80)
PVF-10-26-33	10' x 26'	33	990 (2.21)
PVF-10-32-42	10' x 32'	42	1,260 (2.81)
PVF-10-38-51	10' x 38'	51	1,530 (3.41)
PVF-10-40-54	10' x 40'	54	1,620 (3.61)

PVF-10-44-60	10' x 40'	60	1,800 (4.01)
PVF-10-48-66	10' x 48'	66	1,980 (4.41)

Cast-in-place BayFilter™

For sites requiring more than 66 BFCs or for projects on which a large precast vault or box culvert BayFilter™ is not feasible, BaySaver Technologies, Inc. can supply custom-designed BayFilter™ systems. These custom systems utilize a cast in place vault or other system, and can be designed around specific site constraints. High flow rates, shallow installations, very flat sites, limited footprints, and other design considerations can be addressed with a cast in place system. For more information on custom BayFilter™ designs, please contact BaySaver Technologies, Inc. directly.

Installation of the BayFilter™ System

BayFilter™ systems are installed along with the storm drain. Installation procedures vary depending on the configuration of the BayFilter™ system. Installation instructions for manhole BayFilter™ systems and precast vault BayFilter™ systems are contained in this section.

Custom BayFilter™ systems may have particular installation issues that will be addressed during the design. Installation instruction for a custom BayFilter™ will be included with the custom design documents.

Installation of a BayFilter™ System

1. Contact utility locator to mark any nearby underground utilities and make sure it is safe to excavate.
2. Reference the site plan and stake out the location of the BayFilter™ manhole/vault.
3. Excavate the hole, providing any sheeting and shoring necessary to comply with all federal, state and local safety regulations.
4. Level the subgrade to the proper elevation. Verify the elevation against the manhole/vault dimensions, the invert elevations, and the site plans. Adjust the base aggregate, if necessary.
5. Have the soil bearing capacity verified by a licensed engineer for the required load bearing capacity. On solid subgrade, set the first section of the BayFilter™ manhole/vault.
6. Check the level and elevation of the first section to ensure it is correct before adding any riser sections.
7. If additional section(s) are required, add a watertight seal to the first section of the BayFilter™ manhole/vault. Set additional section(s) of the manhole/vault, adding a watertight seal to each joint.
8. Install the trolley system (if applicable). See separate instruction sheet.
9. Install the PVC outlet manifold. Glue all PVC joints with the exception of the BayFilter cartridge coupling.
10. Install the PVC outlet pipe in BayFilter™ manhole/vault.
11. Install the inlet pipe to the BayFilter™ manhole/vault.
12. Install BayFilter Drain Down Modules (DDM) with red mark aligned to the top of the manifold system.
13. After the site is stabilized, remove any accumulated sediment or debris from the vault and install the flow disks and the BayFilter™ cartridges.

Tool List:

- PVC glue and primer
- Crane / lifting mechanism to lower cartridges in to the vault (each cartridge weighs 350 lb)
- Screwdriver or nut driver for Fernco couplers

- Soft blow hammer
- Saw (in case PVC manifold length needs to be adjusted)

Trolley Installation Instructions

1. Attach the mounting brackets to the track.
2. Mark a horizontal line 6" down from the ceiling of the vault structure on the two long walls.
3. Each track is split in sections. The length and number of sections vary depending on the vault. It is generally better to start installing longer track sections first. Hold a section in place and align the top of the brackets with the horizontal line on the wall. Mark the center of the hole in each bracket and remove the track.
4. Using a hammer drill and 1/4" bit, drill a hole approximately 3" deep at each mark.
5. Hold the track back in place and realign the brackets with the holes. Place a plastic spacer block behind each bracket and using the supplied 1/4" x 3 1/4" anchor bolts mount the track in place. Only install one section of track at this stage.
6. Repeat this procedure on the opposite wall of the vault directly across from the first section.
7. Bolt the 4 trolleys to the aluminum I-beam as shown in the attached diagram. Make sure that the wheels for each trolley are mounted an equal distance from the top of the I-beam.
8. Lift the I-beam in to place and insert the trolleys in to the track.
9. Using the supplied couplers, install the second sections of track via the same procedure. Continue until the track runs the length of the vault or as designed.

Maintenance of the BayFilter™ System

The BayFilter™ system requires periodic maintenance to continue operating at the design efficiency. The maintenance process comprises the removal and replacement of each BayFilter™ cartridge and drain down module and the cleaning of the vault or manhole with a vacuum truck. BayFilter™ maintenance should be performed by a BaySaver Technologies, Inc. certified maintenance contractor.

The maintenance cycle of the BayFilter™ system will be driven mostly by the actual solids load on the filter. The system should be periodically monitored to be certain it is operating correctly. Since stormwater solids loads can be variable, it is possible that the maintenance cycle could be more or less than the projected duration.

The BayFilter systems in New Development applications are designed to treat the WQv in 24 hours initially. Later in the cycle these cartridges will flow at a slower rate, and when the WQv does not drain down within +/- 40 hours after the storm event, the system must be maintained.

When a BayFilter™ system is first installed, it is recommended that it be inspected every six (6) months. When the filter system exhibits flows below design levels the system should be maintained. Filter cartridge replacement should also be considered when sediment levels are at or above the level of the 4 inch manifold system. Please contact the BaySaver Technologies Inc. Engineering Department for maintenance cycle estimations or assistance at 1.800.229.7283.

Maintenance Procedures

1. Remove the manhole covers and open all access hatches.
2. Before entering the system make sure the air is safe per OSHA Standards or use a breathing apparatus. Use low O₂, high CO, or other applicable warning devices per regulatory requirements.
3. Using a vacuum truck remove any liquid and sediments that can be removed prior to entry.
4. Using a small lift or the boom of the vacuum truck, remove the used cartridges by lifting them out.
5. Any cartridges that cannot be readily lifted directly out of the vault should be removed from their location and carried to the lifting point using the Trolley system installed in the Vault (if applicable).
6. When all cartridges and drain down modules are removed, remove the balance of the solids and water; then loosen the stainless clamps on the Fernco couplings in the pipe manifold; remove the drain pipes as well. Carefully cap the manifold and the Fernco's and rinse the floor removing the balance of the collected solids.
7. Clean the manifold pipes, inspect, and reinstall.
8. Install the exchange cartridges and close all covers.
9. The used cartridges must be sent back to BaySaver Technologies, Inc. for exchange/recycling and credit on undamaged units.

BayFilter™ System Costs and Availability

BayFilter™ systems are available throughout the United States from ADS. Material, installation, and maintenance costs can vary significantly with location. For BayFilter™ pricing in your area, please contact ADS at 1-800-821-6710.

BayFilter™ cartridges and outlet components can be shipped anywhere in the continental United States. Manholes and precast vaults are also supplied by BaySaver Technologies, Inc. as part of a complete stormwater filtration system.



BayFilter™ Detailed Operating Sequence

The cycle operation of a BayFilter™ is as follows:

- A.** Vault Fill and Air Release: Water enters the system through an inlet pipe which fills the BayFilter™ vault. As the vault fills, water enters the cartridge through the inlet plate on the bottom.

As the water level rises in the vault, air from inside the BFC is exhausted via an air release valve. This operation is critical for the proper functioning of the siphon, which drives the BayFilter™ during periods of low water level in the vault. (Refer to Figure A-1 for details on this operation).




Figure A-1: Vault filling operation and release

- B. Filtration:** As water enters the continuous inlet drainage spiral, air is exhausted. Water then flows horizontally through the engineered media. Next it flows to the outlet drainage spiral which is also one continuous piece material. Filtered water then flows vertically to the outlet chamber located at the top of the filter media inside of the cartridge. Finally, filtered water flows in to the center outlet drain and leaves the system via the outlet manifold below the inlet plate. (Figure A-2)




Figure A-2: Normal filter operation

- C. Siphon Filtration: After the water level in the vault falls below the top of the filter cartridge, a siphon is established and water will continue to flow (Figure A-3) until the siphon is broken. During siphon the water level in the vault will decrease until it reaches the base of the BFC; air then enters the filter cartridge and breaks the siphon. This cause's filtration flow to stop and hydrodynamic backwash begins.




Figure A-3: Siphon filtration

- D. When air enters the filter, the siphon breaks (Figure A-4), and a gravity-driven backwash occurs with all of the water flowing from the outlet chamber backwards through the filter media (Figure A-5). This backwash has the effect of dislodging particles captured in the filtration layers and re-establishing porosity. Dislodged particles are transported back in to the filter vault and accumulate on the filter vault floor.




Figure A-4: Siphon Break






Figure A-5: Backwash


System Drawings

*NOTE: MANHOLE STEPS CANNOT PROTRUDE MORE THAN
2" INTO 30" OPENING OR CARTRIDGE INSTALLATION
AND REMOVAL MAY BE IMPEDED*




REV	DESCRIPTION	DATE	APPR	NOTES	<div>BAYSAVER TECHNOLOGIES, INC. <small>DESIGNED AND MANUFACTURED IN THE U.S.A.</small> WWW.BAYSAVER.COM</div>	MANHOLE BAYFILTER PROFILE TYPICAL
					DESIGNED: TEP	DATE: 4/30/07
					DRAWN: AJV	SCALE: N.T.S.
					CHECKED: TEP	DWG NO: 001A


BAYFILTER STORMWATER FILTRATION SYSTEM PROTECTED BY U.S. PATENT # 6,869,528




REV	DESCRIPTION	DATE	APPR	NOTES


 BAYSAVER TECHNOLOGIES, INC. WWW.BAYSAVER.COM		VAULT BAYFILTER PROFILE TYPICAL		
DESIGNED:	TEP	DATE:	4/30/07	
DRAWN:	AJW	SCALE:	N.T.S.	
CHECKED:	AJW	DWG NO:	BF-208	


BAYFILTER STORMWATER FILTRATION SYSTEM PROTECTED BY U.S. PATENT # 6,869,528




REV	DESCRIPTION	DATE	APPR	NOTES

 BAYSAYER TECHNOLOGIES, INC. WWW.BAYSAYER.COM		BOX CULVERT BAYFILTER PROFILE TYPICAL		
DESIGNED:	TEP	DATE:	4/30/07	
DRAWN:	AJW	SCALE:	N.T.S.	
CHECKED:	AJW	DWG NO:	BF-209	







PLAN VIEW




SECTION A-A

REV	DESCRIPTION	DATE	APPR	NOTES	 BAYSAVER TECHNOLOGIES, INC. <small>10000 W. 10TH AVE. SUITE 100 DENVER, CO 80202</small> WWW.BAYSAVER.COM	OUTLET HEADER STANDARD DETAIL
DESIGNED: TEP DATE: 5/1/07 DRAWN: AJW SCALE: N.T.S. CHECKED: JAM DWG NO:						


BAYFILTER STORMWATER FILTRATION SYSTEM PROTECTED BY U.S. PATENT # 6,869,328



REV	DESCRIPTION	DATE	APPR	NOTES

 BAYSAVER TECHNOLOGIES, INC. 1000 BAYVIEW BLVD. SUITE 100 BAYVIEW, MI 48008 WWW.BAYSAVER.COM		DESIGNED: TEP DRAWN: EKH CHECKED: EKH	DATE: 11/7/08 SCALE: N.T.S. DWG NO: BF-101
MANHOLE BAYFILTER MODEL MHF-60-3			

BAYFILTER STORMWATER FILTRATION SYSTEM PROTECTED BY U.S. PATENT # 6,869,328





REV	DESCRIPTION	DATE	APPR	NOTES


 BAYSAVER TECHNOLOGIES, INC. <small>STORMWATER FILTRATION SYSTEMS</small> WWW.BAYSAVER.COM		DESIGNED: TEP	DATE: 8/6/08
		DRAWN: EKH	SCALE: N.T.S.
		CHECKED: EKH	DWG NO: BF-102

MANHOLE BAYFILTER
MODEL MHF-72-4


BAYFILTER STORMWATER FILTRATION SYSTEM PROTECTED BY U.S. PATENT # 6,869,328




REV	DESCRIPTION	DATE	APPR	NOTES
<div>  <div> BAYSAVER TECHNOLOGIES, INC. 10000 BAYVIEW BLVD. SUITE 100 DALLAS, TEXAS 75244 WWW.BAYSAVER.COM </div> </div>				
DESIGNED:	TEP	DATE:	3/7/07	
DRAWN:	AJW	SCALE:	N.T.S.	
CHECKED:	AJW	DWG NO:	BF-103	
MANHOLE BAYFILTER MODEL MHF-84-5				



BAYFILTER STORMWATER FILTRATION SYSTEM PROTECTED BY U.S. PATENT # 6,869,528




REV	DESCRIPTION	DATE/APPR	NOTES

 BAYSAVER TECHNOLOGIES, INC. WWW.BAYSAVER.COM		DESIGNED: TEP	DATE: 9/16/08
		DRAWN: EKH	SCALE: N.T.S.
		CHECKED: EKH	DWG NO: BF-207

VAULT BAYFILTER
MODEL PVF-8-10-10

BAYFILTER STORMWATER FILTRATION SYSTEM PROTECTED BY U.S. PATENT # 6,869,528



REV

DESCRIPTION

DATE/APPR

NOTES:



BAYSAVER
TECHNOLOGIES, INC.
WWW.BAYSAVER.COM


DESIGNED: TEP DATE: 9/16/08

DRAWN: EKH SCALE: N.T.S.

CHECKED: EKH DWG NO: BF-208

VAULT BAYFILTER
MODEL PVF-8-12-13

BAYFILTER STORMWATER FILTRATION SYSTEM PROTECTED BY U.S. PATENT # 6,869,528



REV DATE/APPR DESCRIPTION NOTES:




BAYSAYER
TECHNOLOGIES, INC.
WWW.BAYSAYER.COM


DESIGNED:	TEP	DATE:	9/16/08
DRAWN:	EKH	SCALE:	N.T.S.
CHECKED:	EKH	DWG NO:	BF-209

VAULT BAYFILTER
MODEL PVF-8-14-15

BAYFILTER STORMWATER FILTRATION SYSTEM PROTECTED BY U.S. PATENT # 6,869,528




REV	DESCRIPTION	DATE/APPR	NOTES


 BAYSAVER TECHNOLOGIES, INC. WWW.BAYSAVER.COM			
DESIGNED:	TEP	DATE:	3/7/07
DRAWN:	AJW	SCALE:	N.T.S.
CHECKED:	AJW	DWG NO:	BF-210

VAULT BAYFILTER
MODEL PVF-8-16-18

BAYFILTER STORMWATER FILTRATION SYSTEM PROTECTED BY U.S. PATENT # 6,869,588




REV	DESCRIPTION	DATE	APPR	NOTES


<div>  <div> BAYSAVER TECHNOLOGIES, INC. STORMWATER FILTRATION SOLUTIONS WWW.BAYSAVER.COM </div> </div>				
DESIGNED:	TEP	DATE:	11/14/07	
DRAWN:	EKH	SCALE:	N.T.S.	
CHECKED:	AJV	DWG NO:	BF-203	

<div> <div>VAULT BAYFILTER</div> <div>MODEL PVF-10-16-21</div> <div>PRELIMINARY</div> </div>				
--	--	--	--	--

BAYFILTER STORMWATER FILTRATION SYSTEM PROTECTED BY U.S. PATENT # 6,869,588




REV	DESCRIPTION	DATE	APPR	NOTES

 BAYSAVER TECHNOLOGIES, INC. STORMWATER FILTRATION SOLUTIONS WWW.BAYSAVER.COM		DESIGNED: TEP	DATE: 11/14/07
		DRAWN: EKH	SCALE: N.T.S.
		CHECKED: AJV	DWG NO. BF-203

VAULT BAYFILTER MODEL PVF-10-20-27 PRELIMINARY	
--	--

BAYFILTER STORMWATER FILTRATION SYSTEM PROTECTED BY U.S. PATENT # 6,869,588




REV	DESCRIPTION	DATE	APPR	NOTES


BAYSAVER <small>TECHNOLOGIES, INC.</small> <small>STORMWATER FILTRATION SOLUTIONS</small> <small>WWW.BAYSAVER.COM</small>		DESIGNED: TEP DRAWN: EKH CHECKED: AJV	DATE: 11/14/07 SCALE: N.T.S. DWG NO: BF-203
---	--	--	--


VAULT BAYFILTER
 MODEL PVF-10-26-33
 PRELIMINARY

Technical drawing of a 12' x 48' x 36" hatch. The drawing shows a rectangular hatch with a 12' width and 48' length. The hatch is divided into a grid of 12 rows and 4 columns. Each row contains 4 circular openings, and each column contains 12 circular openings. The hatch is labeled with dimensions: 12' OUTLET, 48' x 36" HATCH, RUBBER BEET, 12" TANK AND COVER, and STEPS. A TROLLEY is shown at the bottom center. The hatch is shown in a perspective view, with a 12' x 48' x 36" label at the bottom right.


REV	DESCRIPTION	DATE	APPR	NOTES:	 <p>BAYSAVER TECHNOLOGIES, INC. 10000 BAYVIEW BLVD. SUITE 100 WWW.BAYSAVER.COM</p>	<p>Vault Bayfilter Preliminary Model PVF-10-32-42</p>
					DESIGNED: TEP	DATE: 9/30/08
					DRAWN: EKH	SCALE: N.T.S.
					CHECKED: EKH	DWG NO: BF-204


BAYFILTER STORMWATER FILTRATION SYSTEM PROTECTED BY U.S. PATENT # 6,869,588




REV	DESCRIPTION	DATE	APPR	NOTES	<div>  BAYSAVER TECHNOLOGIES, INC. STORMWATER FILTRATION SOLUTIONS WWW.BAYSAVER.COM </div>			
					DESIGNED: TEP	DATE: 11/14/07	VAULT BAYFILTER MODEL PVF-10-38-51 PRELIMINARY	
					DRAWN: EKH	SCALE: N.T.S.		
					CHECKED: AJV	DWG NO: BF-203		

BAYFILTER STORMWATER FILTRATION SYSTEM PROTECTED BY U.S. PATENT # 6,869,588




REV	DESCRIPTION	DATE	APPR	NOTES:	<div><div>BAYSAYER TECHNOLOGIES, INC. STORMWATER FILTRATION WWW.BAYSAYER.COM</div></div>	VAULT BAYFILTER MODEL PVF-10-40-54 PRELIMINARY
				DESIGNED: TEP	DATE: 9/29/08	
				DRAWN: EKH	SCALE: N.T.S.	
				CHECKED: EKH	DWG NO: BF-203	


BAYFILTER STORMWATER FILTRATION SYSTEM PROTECTED BY U.S. PATENT # 6,869,588



REV	DESCRIPTION	DATE	APPR	NOTES:	DESIGNED: TEP DRAWN: EKH CHECKED: EKH				DATE: 9/29/08 SCALE: N.T.S. DWG NO. BF-203			
					BAYSAYER TECHNOLOGIES, INC. STORMWATER FILTRATION SOLUTIONS WWW.BAYSAYER.COM				VAULT BAYFILTER MODEL PVF-10-44-60 PRELIMINARY			

BAYFILTER STORMWATER FILTRATION SYSTEM PROTECTED BY U.S. PATENT # 6,869,588



REV	DESCRIPTION	DATE	APPR	NOTES	<div>  BAYSAVER TECHNOLOGIES, INC. STORMWATER FILTRATION SOLUTIONS WWW.BAYSAVER.COM </div>			
					DESIGNED:	TEP	DATE:	9/29/08
					DRAWN:	EKH	SCALE:	N.T.S.
					CHECKED:	EKH	DWG NO:	BF-203

VAULT BAYFILTER
MODEL PVF-10-48-66
PRELIMINARY

Project Information Sheet




BayFilter™ Sizing Form

Project Contact Information	
Company Name	Date
Contact Name	<input type="checkbox"/> Engineer <input type="checkbox"/> Developer <input type="checkbox"/> Contractor
Project Name	Email
Telephone	Fax
City	State Zip
Site Characteristics <input type="checkbox"/> Residential <input type="checkbox"/> Commercial <input type="checkbox"/> Industrial <input type="checkbox"/> Mixed	Due Date
Additional comments/project information	
Design and Sizing Parameters	
Total Drainage Area (acres)	Impervious Area (acres)
Required Treatment Flow CFS (if applicable)	Water Quality Volume to be Detained <input type="checkbox"/> 75% <input type="checkbox"/> 100% Other
Water Quality Volume (ft ³)	Project Location: City ST
Regulatory Requirements	
% Total Suspended Solids Removal (ex. 80%)	% Total Phosphorus Removal (ex. 50%)
Project Stage <input type="checkbox"/> Conceptual Design <input type="checkbox"/> Preliminary Design <input type="checkbox"/> Final Design <input type="checkbox"/> Other	
Other Site Specific Sizing Criteria	
Thank you for supplying the required information! You're almost done! We will also need: <div style="margin-left: 40px;"> <input checked="" type="checkbox"/> Plan(s) View <input checked="" type="checkbox"/> Profile(s) </div>	

MKTG0013A#

Please email this form and any drawings to **Engineering@BaySaver.com**
 Phone 800-BAYSAVER (800.229.7283) Fax 301.829.3747




LEGEND:

	EXISTING BUILDING
	EXISTING EASEMENT
	EXISTING WATER EDGE
	EXISTING WETLANDS BUFFER
	EXISTING EDGE OF PAVEMENT
	EXISTING YELLOW LINE
	EXISTING WHITE LINE
	EXISTING OVERHEAD WIRE
	EXISTING WIRE MESH FENCE
	EXISTING SOIL DELINEATOR
	EXISTING PROPERTY LINE
	EXISTING ADJACENT PROPERTY LINE
	EXISTING POND LINE
	EXISTING STONE WALL
	EXISTING DRAINAGE LINE
	EXISTING MAJOR CONTOUR
	EXISTING MINOR CONTOUR
	EXISTING WETLAND
	STEEL BRIDGE
	EXISTING GUY
	RAIL ROAD TRUCK
	GRAVEL SURFACE TO BE REMOVED
	PERCOLATION TEST
	EXISTING WELL
	EXISTING LIGHT POLE
	EXISTING IRON PIPE MARKER
	EXISTING IRON ROD MARKER
	EXISTING RAILROAD SIGNAL X-ING STOP ARM
	EXISTING SIGN
	RR X-ING SIGN
	TREE
	EXISTING TREELINE
	CONCRETE SURFACE

WARNING-- IT IS A VIOLATION OF NEW YORK EDUCATIONAL LAW, SECTION 7209.2, FOR ANY PERSON, UNLESS ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER OR LAND SURVEYOR, TO ALTER THIS DOCUMENT IN ANY WAY. IF ALTERED, THE ALTERING PERSON SHALL COMPLY WITH THE REQUIREMENTS OF NEW YORK EDUCATIONAL LAW, SECTION 7209.2.

ONLY MAPS WITH EMBOSSED SEALS ARE GENUINE COPIES OF THE ORIGINAL WORK AND OPINION. MAPS NOT BEARING EMBOSSED SEALS SHOULD NOT BE RELIED UPON SINCE OTHER THAN EMBOSSED-SEAL COPIES MAY CONTAIN UNAUTHORIZED AND UNDETECTABLE MODIFICATIONS, DELETIONS, ADDITIONS AND CHANGES.

PRE DEVELOPMENT ANALYSIS
SCALE: 1"=100'



Dig Safely. New York
Call811
before you dig

REVISION	BY	DATE	DESCRIPTION


THIS SHEET IS NOT VALID WITHOUT ALL OF THE SHEETS THAT COMPRISE THE SET

ARDEN CONSULTING ENGINEERS, PLLC
P.O. BOX 340 MONROE, N.Y.
TEL: (845) 782-8114
WWW.ARDENCONSULTING.NET

SUBDIVISION & SITE PLAN FOR
1251 KINGS HIGHWAY LLC
1251 KINGS HWY
CHESTER, NY 10918

PRE DEVELOPMENT ANALYSIS

JOB#: 18-029
SCALE: AS NOTED
DATE: 02/25/19
DRAWN: MM
CHECKED: MM
SHEET NO. 01 of 02



	EXISTING BUILDING
	EXISTING WATER EDGE
	EXISTING WETLANDS BUFFER
	EXISTING EDGE OF PAVEMENT
	EXISTING YELLOW LINE
	EXISTING WHITE LINE
	EXISTING OVERHEAD WIRE
	EXISTING PROPERTY LINE
	EXISTING ADJACENT PROPERTY LINE
	EXISTING STONE WALL
	EXISTING MAJOR CONTOUR
	EXISTING MINOR CONTOUR
	EXISTING DRAINAGE LINE
	EXISTING WETLAND
	EXISTING GUY
	GRAVEL SURFACE TO BE REMOVED
	EXISTING RAILROAD SIGNAL X-ING STOP ARM
	PERCOLATION TEST
	EXISTING WELL
	EXISTING LIGHT POLE
	EXISTING IRON PIPE MARKER
	EXISTING IRON ROD MARKER
	EXISTING SIGN
	PROPOSED WELL
	PROPOSED BUILDING
	PROPOSED EDGE OF PAVEMENT
	PROPOSED MAJOR CONTOUR
	PROPOSED MINOR CONTOUR
	PROPOSED SPOT GRADE
	PROPOSED DRAINAGE CATCHBASIN
	PROPOSED DRAINAGE PIPE
	PROPOSED RIPRAP
	PROPOSED PROPERTY LINE


0 40' 80 120 160

SCALE: 1"=40'

REVISION	BY	DATE	DESCRIPTION

THIS SHEET IS NOT VALID WITHOUT ALL OF THE SHEETS THAT COMPRISE THE SET

ARDEN CONSULTING ENGINEERS, PLLC
P.O. BOX 340 MONROE, N.Y.
TEL: (845) 782-8114
WWW.ARDENCONSULTING.NET






POST DEVELOPMENT ANALYSIS

OB#: 18-029
SCALE:
AS NOTED
DATE: 02/25/19
DRAWN: MM
CHECKED: MM
SHEET NO. 02 of 02

MICHAEL A. MORGANTE, P.J.
LIC. NO. 78577

ONLY MAPS WITH EMBOSSED SEALS ARE GENUINE COPIES OF THE ORIGINAL WORK AND OPINION. MAPS NOT BEARING EMBOSSED SEALS SHOULD NOT BE RELIED UPON SINCE OTHER THAN EMBOSSED-SEAL COPIES MAY CONTAIN UNAUTHORIZED AND UNDETECTABLE MODIFICATIONS, DELETIONS, ADDITIONS AND CHANGES.

COPYRIGHT 2018, ARDEN CONSULTING ENGINEERS, P.L.L.C. – ALL RIGHTS RESERVED



Routing Diagram for HYDROCAD 3-13-19

Prepared by Microsoft, Printed 3/17/2019

HydroCAD® 10.00-19 s/n 04164 © 2016 HydroCAD Software Solutions LLC

HYDROCAD 3-13-19

Prepared by Microsoft

Printed 3/17/2019

HydroCAD® 10.00-19 s/n 04164 © 2016 HydroCAD Software Solutions LLC

Page 2

Area Listing (all nodes)

Area (acres)	CN	Description (subcatchment-numbers)
19.050	74	>75% Grass cover, Good, HSG C (1APOST, 1BPOST, 2A POST, 2B POST, 2PRE)
4.247	98	Paved parking, HSG C (1APOST, 2A POST)
8.587	82	Row crops, SR + CR, Good, HSG C (1PRE)
25.034	98	Water Surface, HSG C (1BPOST, 1PRE, 2B POST, 2PRE)
12.889	70	Woods, Good, HSG C (1BPOST, 1PRE, 2PRE)
69.808	84	TOTAL AREA

Soil Listing (all nodes)

Area (acres)	Soil Group	Subcatchment Numbers
0.000	HSG A	
0.000	HSG B	
69.808	HSG C	1APOST, 1BPOST, 1PRE, 2A POST, 2B POST, 2PRE
0.000	HSG D	
0.000	Other	
69.808		TOTAL AREA

HYDROCAD 3-13-19

Prepared by Microsoft

Printed 3/17/2019

HydroCAD® 10.00-19 s/n 04164 © 2016 HydroCAD Software Solutions LLC

Page 4

Ground Covers (all nodes)

HSG-A (acres)	HSG-B (acres)	HSG-C (acres)	HSG-D (acres)	Other (acres)	Total (acres)	Ground Cover	Subcatchment Numbers
0.000	0.000	19.050	0.000	0.000	19.050	>75% Grass cover, Good	1APOS T, 1BPOS T, 2A POST, 2B POST, 2PRE
0.000	0.000	4.247	0.000	0.000	4.247	Paved parking	1APOS T, 2A POST
0.000	0.000	8.587	0.000	0.000	8.587	Row crops, SR + CR, Good	1PRE
0.000	0.000	25.034	0.000	0.000	25.034	Water Surface	1BPOS T, 1PRE, 2B POST, 2PRE
0.000	0.000	12.889	0.000	0.000	12.889	Woods, Good	1BPOS T, 1PRE, 2PRE
0.000	0.000	69.808	0.000	0.000	69.808	TOTAL AREA	

HYDROCAD 3-13-19

Prepared by Microsoft

Printed 3/17/2019

HydroCAD® 10.00-19 s/n 04164 © 2016 HydroCAD Software Solutions LLC

Page 5

Pipe Listing (all nodes)

Line#	Node Number	In-Invert (feet)	Out-Invert (feet)	Length (feet)	Slope (ft/ft)	n	Diam/Width (inches)	Height (inches)	Inside-Fill (inches)
1	IB1	503.00	496.00	460.0	0.0152	0.012	15.0	0.0	0.0
2	SWB2	442.50	441.60	180.0	0.0050	0.012	18.0	0.0	0.0

HYDROCAD 3-13-19

Prepared by Microsoft

HydroCAD® 10.00-19 s/n 04164 © 2016 HydroCAD Software Solutions LLC

Type III 24-hr 1 YR Rainfall=2.70"

Printed 3/17/2019

Page 6

Time span=0.00-24.00 hrs, dt=0.01 hrs, 2401 points

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN

Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

Subcatchment1APOST: WATERSHED 1A Runoff Area=150,150 sf 59.94% Impervious Runoff Depth>1.55"
Flow Length=560' Tc=6.0 min CN=88 Runoff=6.28 cfs 0.446 af

Subcatchment1BPOST: WATERSHED 1B Runoff Area=540,790 sf 20.94% Impervious Runoff Depth>0.92"
Flow Length=490' Tc=10.3 min CN=78 Runoff=11.03 cfs 0.950 af

Subcatchment1PRE: WATERSHED 1 PRE Runoff Area=690,940 sf 16.39% Impervious Runoff Depth>1.08"
Flow Length=490' Tc=12.4 min CN=81 Runoff=16.03 cfs 1.433 af

Subcatchment2A POST: WATERSHED Runoff Area=193,390 sf 49.12% Impervious Runoff Depth>1.41"
Flow Length=395' Tc=7.4 min CN=86 Runoff=6.98 cfs 0.520 af

Subcatchment2B POST: WATERSHED Runoff Area=635,992 sf 67.64% Impervious Runoff Depth>1.71"
Flow Length=300' Tc=10.8 min CN=90 Runoff=24.86 cfs 2.077 af

Subcatchment2PRE: WATERSHED 2 PRE Runoff Area=829,559 sf 52.29% Impervious Runoff Depth>1.40"
Flow Length=630' Tc=12.6 min CN=86 Runoff=25.37 cfs 2.230 af

Reach DP1: DP1

Inflow=11.03 cfs 0.950 af

Outflow=11.03 cfs 0.950 af

Reach DP2: DP2

Inflow=24.86 cfs 2.253 af

Outflow=24.86 cfs 2.253 af

Pond IB1: INFILTRATION BASIN 1

Peak Elev=503.05' Storage=5,473 cf Inflow=6.11 cfs 0.366 af

Discarded=0.94 cfs 0.366 af Primary=0.00 cfs 0.000 af Secondary=0.00 cfs 0.000 af Outflow=0.94 cfs 0.366 af

Pond SB1: SEDIMENTATION BASIN 1

Peak Elev=503.80' Storage=4,089 cf Inflow=6.28 cfs 0.446 af

Outflow=6.11 cfs 0.366 af

Pond SWB2: STORMWATER BASIN 2

Peak Elev=443.55' Storage=15,892 cf Inflow=6.98 cfs 0.520 af

Primary=0.36 cfs 0.176 af Secondary=0.00 cfs 0.000 af Outflow=0.36 cfs 0.176 af

Total Runoff Area = 69.808 ac Runoff Volume = 7.656 af Average Runoff Depth = 1.32"
58.05% Pervious = 40.526 ac 41.95% Impervious = 29.281 ac


Summary for Subcatchment 1APOST: WATERSHED 1A POST

Runoff = 6.28 cfs @ 12.09 hrs, Volume= 0.446 af, Depth> 1.55"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type III 24-hr 1 YR Rainfall=2.70"

Area (sf)	CN	Description
90,000	98	Paved parking, HSG C
60,150	74	>75% Grass cover, Good, HSG C
150,150	88	Weighted Average
60,150		40.06% Pervious Area
90,000		59.94% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
0.7	100	0.0900	2.53		Sheet Flow, Sheet Flow
					Smooth surfaces n= 0.011 P2= 3.25"
2.7	460	0.0200	2.87		Shallow Concentrated Flow, Shallow Flow to SW Basin
					Paved Kv= 20.3 fps
3.4	560	Total, Increased to minimum Tc = 6.0 min			

Subcatchment 1APOST: WATERSHED 1A POST


Summary for Subcatchment 1BPOST: WATERSHED 1B POST

Runoff = 11.03 cfs @ 12.15 hrs, Volume= 0.950 af, Depth> 0.92"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type III 24-hr 1 YR Rainfall=2.70"

Area (sf)	CN	Description
113,266	98	Water Surface, HSG C
277,724	74	>75% Grass cover, Good, HSG C
149,800	70	Woods, Good, HSG C
540,790	78	Weighted Average
427,524		79.06% Pervious Area
113,266		20.94% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.4	100	0.0400	0.23		Sheet Flow, Sheet Flow Grass: Short n= 0.150 P2= 3.25"
1.3	205	0.1500	2.71		Shallow Concentrated Flow, Shallow Flow to Woods Short Grass Pasture Kv= 7.0 fps
1.6	185	0.1400	1.87		Shallow Concentrated Flow, Shallow Flow Woods to Wetland Woodland Kv= 5.0 fps
10.3	490	Total			

Subcatchment 1BPOST: WATERSHED 1B POST


Summary for Subcatchment 1PRE: WATERSHED 1 PRE

Runoff = 16.03 cfs @ 12.18 hrs, Volume= 1.433 af, Depth> 1.08"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type III 24-hr 1 YR Rainfall=2.70"

Area (sf)	CN	Description
113,266	98	Water Surface, HSG C
374,041	82	Row crops, SR + CR, Good, HSG C
203,633	70	Woods, Good, HSG C
690,940	81	Weighted Average
577,674		83.61% Pervious Area
113,266		16.39% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
8.1	100	0.0400	0.20		Sheet Flow, Sheet Flow Cultivated: Residue>20% n= 0.170 P2= 3.25"
1.0	205	0.1500	3.49		Shallow Concentrated Flow, Shallow Flow to Woods Cultivated Straight Rows Kv= 9.0 fps
3.3	185	0.1400	0.94		Shallow Concentrated Flow, Shallow Flow Woods to Wetland Forest w/Heavy Litter Kv= 2.5 fps
12.4	490	Total			

Subcatchment 1PRE: WATERSHED 1 PRE

HYDROCAD 3-13-19

Prepared by Microsoft

HydroCAD® 10.00-19 s/n 04164 © 2016 HydroCAD Software Solutions LLC

Type III 24-hr 1 YR Rainfall=2.70"

Printed 3/17/2019

Page 10


Summary for Subcatchment 2A POST: WATERSHED 2A POST

Runoff = 6.98 cfs @ 12.11 hrs, Volume= 0.520 af, Depth> 1.41"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type III 24-hr 1 YR Rainfall=2.70"

Area (sf)	CN	Description
98,390	74	>75% Grass cover, Good, HSG C
95,000	98	Paved parking, HSG C
193,390	86	Weighted Average
98,390		50.88% Pervious Area
95,000		49.12% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.6	100	0.0800	0.30		Sheet Flow, Sheet Flow Grass: Short n= 0.150 P2= 3.25"
0.4	60	0.1500	2.71		Shallow Concentrated Flow, Shallow Flow to Pavement Short Grass Pasture Kv= 7.0 fps
1.4	235	0.0200	2.87		Shallow Concentrated Flow, Shallow Flow Pavement to Catchbasin Paved Kv= 20.3 fps
7.4	395	Total			

Subcatchment 2A POST: WATERSHED 2A POST


Summary for Subcatchment 2B POST: WATERSHED 2B POST

Runoff = 24.86 cfs @ 12.15 hrs, Volume= 2.077 af, Depth> 1.71"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type III 24-hr 1 YR Rainfall=2.70"

Area (sf)	CN	Description
205,792	74	>75% Grass cover, Good, HSG C
430,200	98	Water Surface, HSG C
635,992	90	Weighted Average
205,792		32.36% Pervious Area
430,200		67.64% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
8.9	100	0.0250	0.19		Sheet Flow, Sheet Flow
					Grass: Short n= 0.150 P2= 3.25"
1.9	200	0.0650	1.78		Shallow Concentrated Flow, Shallow Flow to Wetland
					Short Grass Pasture Kv= 7.0 fps
10.8	300	Total			

Subcatchment 2B POST: WATERSHED 2B POST


Summary for Subcatchment 2PRE: WATERSHED 2 PRE

Runoff = 25.37 cfs @ 12.17 hrs, Volume= 2.230 af, Depth> 1.40"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type III 24-hr 1 YR Rainfall=2.70"

Area (sf)	CN	Description
187,773	74	>75% Grass cover, Good, HSG C
433,755	98	Water Surface, HSG C
208,031	70	Woods, Good, HSG C
829,559	86	Weighted Average
395,804		47.71% Pervious Area
433,755		52.29% Impervious Area


Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.3	100	0.0600	0.27		Sheet Flow, Sheet Flow
					Grass: Short n= 0.150 P2= 3.25"
6.3	530	0.0400	1.40		Shallow Concentrated Flow, Shallow Flow to Wetland
					Short Grass Pasture Kv= 7.0 fps
12.6	630	Total			

Subcatchment 2PRE: WATERSHED 2 PRE

Summary for Reach DP1: DP1

Inflow Area = 15.862 ac, 29.42% Impervious, Inflow Depth > 0.72" for 1 YR event
Inflow = 11.03 cfs @ 12.15 hrs, Volume= 0.950 af
Outflow = 11.03 cfs @ 12.15 hrs, Volume= 0.950 af, Atten= 0%, Lag= 0.0 min

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Reach DP1: DP1


Summary for Reach DP2: DP2

Inflow Area = 19.040 ac, 63.32% Impervious, Inflow Depth > 1.42" for 1 YR event
Inflow = 24.86 cfs @ 12.15 hrs, Volume= 2.253 af
Outflow = 24.86 cfs @ 12.15 hrs, Volume= 2.253 af, Atten= 0%, Lag= 0.0 min

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Reach DP2: DP2

Hydrograph



Summary for Pond IB1: INFILTRATION BASIN 1

Inflow Area = 3.447 ac, 59.94% Impervious, Inflow Depth > 1.27" for 1 YR event
 Inflow = 6.11 cfs @ 12.11 hrs, Volume= 0.366 af
 Outflow = 0.94 cfs @ 12.65 hrs, Volume= 0.366 af, Atten= 85%, Lag= 32.8 min
 Discarded = 0.94 cfs @ 12.65 hrs, Volume= 0.366 af
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af
 Secondary = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 503.05' @ 12.65 hrs Surf.Area= 5,422 sf Storage= 5,473 cf
 Flood Elev= 506.50' Surf.Area= 10,500 sf Storage= 31,452 cf

Plug-Flow detention time= (not calculated: outflow precedes inflow)
 Center-of-Mass det. time= 52.3 min (909.1 - 856.8)

Volume	Invert	Avail.Storage	Storage Description		
#1	502.00'	31,452 cf	Custom Stage Data (Irregular) Listed below (Recalc)		
Elevation (feet)	Surf.Area (sq-ft)	Perim. (feet)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)	Wet.Area (sq-ft)
502.00	4,965	280.0	0	0	4,965
504.00	5,850	300.0	10,803	10,803	6,055
506.00	9,880	450.0	15,555	26,358	15,039
506.50	10,500	465.0	5,094	31,452	16,155

Device	Routing	Invert	Outlet Devices
#1	Primary	503.00'	15.0" Round Culvert L= 460.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 503.00' / 496.00' S= 0.0152 ' /' Cc= 0.900 n= 0.012, Flow Area= 1.23 sf
#2	Discarded	502.00'	5.000 in/hr Exfiltration over Surface area Conductivity to Groundwater Elevation = 500.00'
#3	Device 1	504.00'	Custom Weir/Orifice X 4.00, Cv= 2.62 (C= 3.28) Head (feet) 0.00 1.50 Width (feet) 2.00 2.00
#4	Device 1	505.50'	30.0" x 48.0" Horiz. Orifice/Grate C= 0.600 in 42.0" x 60.0" Grate (57% open area) Limited to weir flow at low heads
#5	Secondary	506.30'	15.0' long x 5.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 5.00 5.50 Coef. (English) 2.34 2.50 2.70 2.68 2.68 2.66 2.65 2.65 2.65 2.65 2.67 2.66 2.68 2.70 2.74 2.79 2.88

Discarded OutFlow Max=0.94 cfs @ 12.65 hrs HW=503.05' (Free Discharge)

↳ **2=Exfiltration** (Controls 0.94 cfs)

Primary OutFlow Max=0.00 cfs @ 0.00 hrs HW=502.00' TW=0.00' (Dynamic Tailwater)

↳ **1=Culvert** (Controls 0.00 cfs)


↳ **3=Custom Weir/Orifice** (Controls 0.00 cfs)

↳ **4=Orifice/Grate** (Controls 0.00 cfs)

Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=502.00' TW=0.00' (Dynamic Tailwater)

↳ **5=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)

Pond IB1: INFILTRATION BASIN 1



Summary for Pond SB1: SEDIMENTATION BASIN 1

Inflow Area = 3.447 ac, 59.94% Impervious, Inflow Depth > 1.55" for 1 YR event
 Inflow = 6.28 cfs @ 12.09 hrs, Volume= 0.446 af
 Outflow = 6.11 cfs @ 12.11 hrs, Volume= 0.366 af, Atten= 3%, Lag= 1.2 min
 Primary = 6.11 cfs @ 12.11 hrs, Volume= 0.366 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 503.80' @ 12.11 hrs Surf.Area= 2,217 sf Storage= 4,089 cf
 Flood Elev= 506.50' Surf.Area= 2,340 sf Storage= 4,534 cf


Plug-Flow detention time= 107.2 min calculated for 0.366 af (82% of inflow)
 Center-of-Mass det. time= 35.3 min (856.8 - 821.5)

Volume	Invert	Avail.Storage	Storage Description
#1	501.00'	4,534 cf	Custom Stage Data (Irregular) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Perim. (feet)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)	Wet.Area (sq-ft)
501.00	800	130.0	0	0	800
502.00	1,240	160.0	1,012	1,012	1,507
504.00	2,340	220.0	3,522	4,534	3,361

Device	Routing	Invert	Outlet Devices
#1	Primary	503.50'	15.0' long x 5.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 5.00 5.50 Coef. (English) 2.34 2.50 2.70 2.68 2.68 2.66 2.65 2.65 2.65 2.65 2.67 2.66 2.68 2.70 2.74 2.79 2.88

Primary OutFlow Max=6.10 cfs @ 12.11 hrs HW=503.80' TW=502.37' (Dynamic Tailwater)
 ↑1=Broad-Crested Rectangular Weir (Weir Controls 6.10 cfs @ 1.34 fps)

Pond SB1: SEDIMENTATION BASIN 1

Summary for Pond SWB2: STORMWATER BASIN 2

Inflow Area = 4.440 ac, 49.12% Impervious, Inflow Depth > 1.41" for 1 YR event
 Inflow = 6.98 cfs @ 12.11 hrs, Volume= 0.520 af
 Outflow = 0.36 cfs @ 15.13 hrs, Volume= 0.176 af, Atten= 95%, Lag= 181.3 min
 Primary = 0.36 cfs @ 15.13 hrs, Volume= 0.176 af
 Secondary = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 443.55' @ 15.13 hrs Surf.Area= 9,296 sf Storage= 15,892 cf
 Flood Elev= 446.00' Surf.Area= 14,315 sf Storage= 44,478 cf

Plug-Flow detention time= 365.2 min calculated for 0.176 af (34% of inflow)
 Center-of-Mass det. time= 238.1 min (1,068.6 - 830.5)

Volume	Invert	Avail.Storage	Storage Description		
#1	441.50'	44,478 cf	Custom Stage Data (Irregular) Listed below (Recalc)		
Elevation (feet)	Surf.Area (sq-ft)	Perim. (feet)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)	Wet.Area (sq-ft)
441.50	6,320	601.0	0	0	6,320
444.00	10,030	660.0	20,260	20,260	12,447
446.00	14,315	725.0	24,218	44,478	19,743


Device	Routing	Invert	Outlet Devices
#1	Primary	442.50'	18.0" Round Culvert L= 180.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 442.50' / 441.60' S= 0.0050 ' S= 0.0050 ' Cc= 0.900 n= 0.012, Flow Area= 1.77 sf
#2	Primary	443.00'	3.0" Vert. Orifice/Grate C= 0.600
#3	Device 1	443.50'	Custom Weir/Orifice X 4.00, Cv= 2.62 (C= 3.28) Head (feet) 0.00 2.00 Width (feet) 1.50 1.50
#4	Device 1	445.50'	30.0" x 48.0" Horiz. Orifice/Grate C= 0.600 in 42.0" x 60.0" Grate (57% open area) Limited to weir flow at low heads
#5	Secondary	445.50'	10.0' long x 5.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 5.00 5.50 Coef. (English) 2.34 2.50 2.70 2.68 2.68 2.66 2.65 2.65 2.65 2.65 2.67 2.66 2.68 2.70 2.74 2.79 2.88

Primary OutFlow Max=0.36 cfs @ 15.13 hrs HW=443.55' TW=0.00' (Dynamic Tailwater)

1=Culvert (Passes 0.21 cfs of 3.96 cfs potential flow)
 3=Custom Weir/Orifice (Weir Controls 0.21 cfs @ 0.72 fps)
 4=Orifice/Grate (Controls 0.00 cfs)
 2=Orifice/Grate (Orifice Controls 0.15 cfs @ 3.13 fps)

Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=441.50' TW=0.00' (Dynamic Tailwater)

5=Broad-Crested Rectangular Weir (Controls 0.00 cfs)

Pond SWB2: STORMWATER BASIN 2

Time span=0.00-24.00 hrs, dt=0.01 hrs, 2401 points

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN

Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

Subcatchment1APOST: WATERSHED 1A Runoff Area=150,150 sf 59.94% Impervious Runoff Depth>3.43"
Flow Length=560' Tc=6.0 min CN=88 Runoff=13.59 cfs 0.985 af

Subcatchment1BPOST: WATERSHED 1B Runoff Area=540,790 sf 20.94% Impervious Runoff Depth>2.50"
Flow Length=490' Tc=10.3 min CN=78 Runoff=31.49 cfs 2.582 af

Subcatchment1PRE: WATERSHED 1 PRE Runoff Area=690,940 sf 16.39% Impervious Runoff Depth>2.76"
Flow Length=490' Tc=12.4 min CN=81 Runoff=41.80 cfs 3.647 af

Subcatchment2A POST: WATERSHED Runoff Area=193,390 sf 49.12% Impervious Runoff Depth>3.23"
Flow Length=395' Tc=7.4 min CN=86 Runoff=15.86 cfs 1.195 af

Subcatchment2B POST: WATERSHED Runoff Area=635,992 sf 67.64% Impervious Runoff Depth>3.63"
Flow Length=300' Tc=10.8 min CN=90 Runoff=51.47 cfs 4.416 af

Subcatchment2PRE: WATERSHED 2 PRE Runoff Area=829,559 sf 52.29% Impervious Runoff Depth>3.23"
Flow Length=630' Tc=12.6 min CN=86 Runoff=57.84 cfs 5.122 af

Reach DP1: DP1

Inflow=31.49 cfs 2.706 af

Outflow=31.49 cfs 2.706 af

Reach DP2: DP2

Inflow=57.47 cfs 5.253 af

Outflow=57.47 cfs 5.253 af

Pond IB1: INFILTRATION BASIN 1 Peak Elev=504.28' Storage=12,500 cf Inflow=13.37 cfs 0.905 af
Discarded=1.44 cfs 0.781 af Primary=3.85 cfs 0.124 af Secondary=0.00 cfs 0.000 af Outflow=5.29 cfs 0.905 af

Pond SB1: SEDIMENTATION BASIN 1 Peak Elev=504.29' Storage=4,534 cf Inflow=13.59 cfs 0.985 af
Outflow=13.37 cfs 0.905 af

Pond SWB2: STORMWATER BASIN 2 Peak Elev=444.09' Storage=21,172 cf Inflow=15.86 cfs 1.195 af
Primary=7.43 cfs 0.837 af Secondary=0.00 cfs 0.000 af Outflow=7.43 cfs 0.837 af

Total Runoff Area = 69.808 ac Runoff Volume = 17.946 af Average Runoff Depth = 3.08"
58.05% Pervious = 40.526 ac 41.95% Impervious = 29.281 ac


Summary for Subcatchment 1APOST: WATERSHED 1A POST

Runoff = 13.59 cfs @ 12.09 hrs, Volume= 0.985 af, Depth> 3.43"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type III 24-hr 10 YR Rainfall=4.75"

Area (sf)	CN	Description
90,000	98	Paved parking, HSG C
60,150	74	>75% Grass cover, Good, HSG C
150,150	88	Weighted Average
60,150		40.06% Pervious Area
90,000		59.94% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
0.7	100	0.0900	2.53		Sheet Flow, Sheet Flow Smooth surfaces n= 0.011 P2= 3.25"
2.7	460	0.0200	2.87		Shallow Concentrated Flow, Shallow Flow to SW Basin Paved Kv= 20.3 fps
3.4	560	Total, Increased to minimum Tc = 6.0 min			

Subcatchment 1APOST: WATERSHED 1A POST


Summary for Subcatchment 1BPOST: WATERSHED 1B POST

Runoff = 31.49 cfs @ 12.14 hrs, Volume= 2.582 af, Depth> 2.50"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type III 24-hr 10 YR Rainfall=4.75"

Area (sf)	CN	Description
113,266	98	Water Surface, HSG C
277,724	74	>75% Grass cover, Good, HSG C
149,800	70	Woods, Good, HSG C
540,790	78	Weighted Average
427,524		79.06% Pervious Area
113,266		20.94% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.4	100	0.0400	0.23		Sheet Flow, Sheet Flow Grass: Short n= 0.150 P2= 3.25"
1.3	205	0.1500	2.71		Shallow Concentrated Flow, Shallow Flow to Woods Short Grass Pasture Kv= 7.0 fps
1.6	185	0.1400	1.87		Shallow Concentrated Flow, Shallow Flow Woods to Wetland Woodland Kv= 5.0 fps
10.3	490	Total			

Subcatchment 1BPOST: WATERSHED 1B POST


Summary for Subcatchment 1PRE: WATERSHED 1 PRE

Runoff = 41.80 cfs @ 12.17 hrs, Volume= 3.647 af, Depth> 2.76"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type III 24-hr 10 YR Rainfall=4.75"

Area (sf)	CN	Description
113,266	98	Water Surface, HSG C
374,041	82	Row crops, SR + CR, Good, HSG C
203,633	70	Woods, Good, HSG C
690,940	81	Weighted Average
577,674		83.61% Pervious Area
113,266		16.39% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
8.1	100	0.0400	0.20		Sheet Flow, Sheet Flow Cultivated: Residue>20% n= 0.170 P2= 3.25"
1.0	205	0.1500	3.49		Shallow Concentrated Flow, Shallow Flow to Woods Cultivated Straight Rows Kv= 9.0 fps
3.3	185	0.1400	0.94		Shallow Concentrated Flow, Shallow Flow Woods to Wetland Forest w/Heavy Litter Kv= 2.5 fps
12.4	490	Total			

Subcatchment 1PRE: WATERSHED 1 PRE


Summary for Subcatchment 2A POST: WATERSHED 2A POST

Runoff = 15.86 cfs @ 12.10 hrs, Volume= 1.195 af, Depth> 3.23"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type III 24-hr 10 YR Rainfall=4.75"

Area (sf)	CN	Description
98,390	74	>75% Grass cover, Good, HSG C
95,000	98	Paved parking, HSG C
193,390	86	Weighted Average
98,390		50.88% Pervious Area
95,000		49.12% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.6	100	0.0800	0.30		Sheet Flow, Sheet Flow Grass: Short n= 0.150 P2= 3.25"
0.4	60	0.1500	2.71		Shallow Concentrated Flow, Shallow Flow to Pavement Short Grass Pasture Kv= 7.0 fps
1.4	235	0.0200	2.87		Shallow Concentrated Flow, Shallow Flow Pavement to Catchba Paved Kv= 20.3 fps
7.4	395	Total			

Subcatchment 2A POST: WATERSHED 2A POST


Summary for Subcatchment 2B POST: WATERSHED 2B POST

Runoff = 51.47 cfs @ 12.15 hrs, Volume= 4.416 af, Depth> 3.63"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type III 24-hr 10 YR Rainfall=4.75"

Area (sf)	CN	Description
205,792	74	>75% Grass cover, Good, HSG C
430,200	98	Water Surface, HSG C
635,992	90	Weighted Average
205,792		32.36% Pervious Area
430,200		67.64% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
8.9	100	0.0250	0.19		Sheet Flow, Sheet Flow
					Grass: Short n= 0.150 P2= 3.25"
1.9	200	0.0650	1.78		Shallow Concentrated Flow, Shallow Flow to Wetland
					Short Grass Pasture Kv= 7.0 fps
10.8	300	Total			

Subcatchment 2B POST: WATERSHED 2B POST


Summary for Subcatchment 2PRE: WATERSHED 2 PRE

Runoff = 57.84 cfs @ 12.17 hrs, Volume= 5.122 af, Depth> 3.23"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type III 24-hr 10 YR Rainfall=4.75"

Area (sf)	CN	Description
187,773	74	>75% Grass cover, Good, HSG C
433,755	98	Water Surface, HSG C
208,031	70	Woods, Good, HSG C
829,559	86	Weighted Average
395,804		47.71% Pervious Area
433,755		52.29% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.3	100	0.0600	0.27		Sheet Flow, Sheet Flow
					Grass: Short n= 0.150 P2= 3.25"
6.3	530	0.0400	1.40		Shallow Concentrated Flow, Shallow Flow to Wetland
					Short Grass Pasture Kv= 7.0 fps
12.6	630	Total			

Subcatchment 2PRE: WATERSHED 2 PRE

Summary for Reach DP1: DP1

Inflow Area = 15.862 ac, 29.42% Impervious, Inflow Depth > 2.05" for 10 YR event


Inflow = 31.49 cfs @ 12.14 hrs, Volume= 2.706 af

Outflow = 31.49 cfs @ 12.14 hrs, Volume= 2.706 af, Atten= 0%, Lag= 0.0 min

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Reach DP1: DP1


Hydrograph



Summary for Reach DP2: DP2

Inflow Area = 19.040 ac, 63.32% Impervious, Inflow Depth > 3.31" for 10 YR event
Inflow = 57.47 cfs @ 12.16 hrs, Volume= 5.253 af
Outflow = 57.47 cfs @ 12.16 hrs, Volume= 5.253 af, Atten= 0%, Lag= 0.0 min

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Reach DP2: DP2

Summary for Pond IB1: INFILTRATION BASIN 1

Inflow Area = 3.447 ac, 59.94% Impervious, Inflow Depth > 3.15" for 10 YR event
 Inflow = 13.37 cfs @ 12.10 hrs, Volume= 0.905 af
 Outflow = 5.29 cfs @ 12.32 hrs, Volume= 0.905 af, Atten= 60%, Lag= 13.6 min
 Discarded = 1.44 cfs @ 12.32 hrs, Volume= 0.781 af
 Primary = 3.85 cfs @ 12.32 hrs, Volume= 0.124 af
 Secondary = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 504.28' @ 12.32 hrs Surf.Area= 6,348 sf Storage= 12,500 cf
 Flood Elev= 506.50' Surf.Area= 10,500 sf Storage= 31,452 cf

Plug-Flow detention time= (not calculated: outflow precedes inflow)
 Center-of-Mass det. time= 79.2 min (904.4 - 825.2)

Volume	Invert	Avail.Storage	Storage Description		
#1	502.00'	31,452 cf	Custom Stage Data (Irregular) Listed below (Recalc)		
Elevation (feet)	Surf.Area (sq-ft)	Perim. (feet)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)	Wet.Area (sq-ft)
502.00	4,965	280.0	0	0	4,965
504.00	5,850	300.0	10,803	10,803	6,055
506.00	9,880	450.0	15,555	26,358	15,039
506.50	10,500	465.0	5,094	31,452	16,155

Device	Routing	Invert	Outlet Devices
#1	Primary	503.00'	15.0" Round Culvert L= 460.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 503.00' / 496.00' S= 0.0152 ' /' Cc= 0.900 n= 0.012, Flow Area= 1.23 sf
#2	Discarded	502.00'	5.000 in/hr Exfiltration over Surface area Conductivity to Groundwater Elevation = 500.00'
#3	Device 1	504.00'	Custom Weir/Orifice X 4.00, Cv= 2.62 (C= 3.28) Head (feet) 0.00 1.50 Width (feet) 2.00 2.00
#4	Device 1	505.50'	30.0" x 48.0" Horiz. Orifice/Grate C= 0.600 in 42.0" x 60.0" Grate (57% open area) Limited to weir flow at low heads
#5	Secondary	506.30'	15.0' long x 5.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 5.00 5.50 Coef. (English) 2.34 2.50 2.70 2.68 2.68 2.66 2.65 2.65 2.65 2.65 2.67 2.66 2.68 2.70 2.74 2.79 2.88

Discarded OutFlow Max=1.44 cfs @ 12.32 hrs HW=504.28' (Free Discharge)

↳ **2=Exfiltration** (Controls 1.44 cfs)

Primary OutFlow Max=3.85 cfs @ 12.32 hrs HW=504.28' TW=0.00' (Dynamic Tailwater)

↳ **1=Culvert** (Passes 3.85 cfs of 4.78 cfs potential flow)


↳ **3=Custom Weir/Orifice** (Weir Controls 3.85 cfs @ 1.73 fps)

↳ **4=Orifice/Grate** (Controls 0.00 cfs)

Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=502.00' TW=0.00' (Dynamic Tailwater)

↳ **5=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)

Pond IB1: INFILTRATION BASIN 1



Summary for Pond SB1: SEDIMENTATION BASIN 1

Inflow Area = 3.447 ac, 59.94% Impervious, Inflow Depth > 3.43" for 10 YR event
 Inflow = 13.59 cfs @ 12.09 hrs, Volume= 0.985 af
 Outflow = 13.37 cfs @ 12.10 hrs, Volume= 0.905 af, Atten= 2%, Lag= 0.6 min
 Primary = 13.37 cfs @ 12.10 hrs, Volume= 0.905 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 504.29' @ 12.32 hrs Surf.Area= 2,340 sf Storage= 4,534 cf
 Flood Elev= 506.50' Surf.Area= 2,340 sf Storage= 4,534 cf


Plug-Flow detention time= 67.3 min calculated for 0.904 af (92% of inflow)
 Center-of-Mass det. time= 26.1 min (825.2 - 799.1)

Volume	Invert	Avail.Storage	Storage Description
#1	501.00'	4,534 cf	Custom Stage Data (Irregular) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Perim. (feet)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)	Wet.Area (sq-ft)
501.00	800	130.0	0	0	800
502.00	1,240	160.0	1,012	1,012	1,507
504.00	2,340	220.0	3,522	4,534	3,361

Device	Routing	Invert	Outlet Devices
#1	Primary	503.50'	15.0' long x 5.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 5.00 5.50 Coef. (English) 2.34 2.50 2.70 2.68 2.68 2.66 2.65 2.65 2.65 2.65 2.67 2.66 2.68 2.70 2.74 2.79 2.88

Primary OutFlow Max=13.04 cfs @ 12.10 hrs HW=503.99' TW=503.57' (Dynamic Tailwater)
 ↑1=Broad-Crested Rectangular Weir (Weir Controls 13.04 cfs @ 1.77 fps)

Pond SB1: SEDIMENTATION BASIN 1

Summary for Pond SWB2: STORMWATER BASIN 2

Inflow Area = 4.440 ac, 49.12% Impervious, Inflow Depth > 3.23" for 10 YR event
 Inflow = 15.86 cfs @ 12.10 hrs, Volume= 1.195 af
 Outflow = 7.43 cfs @ 12.30 hrs, Volume= 0.837 af, Atten= 53%, Lag= 11.9 min
 Primary = 7.43 cfs @ 12.30 hrs, Volume= 0.837 af
 Secondary = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 444.09' @ 12.30 hrs Surf.Area= 10,207 sf Storage= 21,172 cf
 Flood Elev= 446.00' Surf.Area= 14,315 sf Storage= 44,478 cf

Plug-Flow detention time= 163.8 min calculated for 0.837 af (70% of inflow)
 Center-of-Mass det. time= 71.2 min (878.1 - 806.9)

Volume	Invert	Avail.Storage	Storage Description		
#1	441.50'	44,478 cf	Custom Stage Data (Irregular) Listed below (Recalc)		
Elevation (feet)	Surf.Area (sq-ft)	Perim. (feet)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)	Wet.Area (sq-ft)
441.50	6,320	601.0	0	0	6,320
444.00	10,030	660.0	20,260	20,260	12,447
446.00	14,315	725.0	24,218	44,478	19,743


Device	Routing	Invert	Outlet Devices
#1	Primary	442.50'	18.0" Round Culvert L= 180.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 442.50' / 441.60' S= 0.0050 ' Cc= 0.900 n= 0.012, Flow Area= 1.77 sf
#2	Primary	443.00'	3.0" Vert. Orifice/Grate C= 0.600
#3	Device 1	443.50'	Custom Weir/Orifice X 4.00, Cv= 2.62 (C= 3.28) Head (feet) 0.00 2.00 Width (feet) 1.50 1.50
#4	Device 1	445.50'	30.0" x 48.0" Horiz. Orifice/Grate C= 0.600 in 42.0" x 60.0" Grate (57% open area) Limited to weir flow at low heads
#5	Secondary	445.50'	10.0' long x 5.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 5.00 5.50 Coef. (English) 2.34 2.50 2.70 2.68 2.68 2.66 2.65 2.65 2.65 2.65 2.67 2.66 2.68 2.70 2.74 2.79 2.88

Primary OutFlow Max=7.43 cfs @ 12.30 hrs HW=444.09' TW=0.00' (Dynamic Tailwater)

1=Culvert (Barrel Controls 7.20 cfs @ 4.78 fps)
 3=Custom Weir/Orifice (Passes 7.20 cfs of 8.91 cfs potential flow)
 4=Orifice/Grate (Controls 0.00 cfs)
 2=Orifice/Grate (Orifice Controls 0.23 cfs @ 4.73 fps)

Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=441.50' TW=0.00' (Dynamic Tailwater)

5=Broad-Crested Rectangular Weir (Controls 0.00 cfs)

Pond SWB2: STORMWATER BASIN 2

HYDROCAD 3-13-19

Prepared by Microsoft

HydroCAD® 10.00-19 s/n 04164 © 2016 HydroCAD Software Solutions LLC

Type III 24-hr 100 YR Rainfall=8.50"

Printed 3/17/2019

Page 36

Time span=0.00-24.00 hrs, dt=0.01 hrs, 2401 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

Subcatchment1APOST: WATERSHED 1A Runoff Area=150,150 sf 59.94% Impervious Runoff Depth>7.05"
Flow Length=560' Tc=6.0 min CN=88 Runoff=26.92 cfs 2.025 af

Subcatchment1BPOST: WATERSHED 1B Runoff Area=540,790 sf 20.94% Impervious Runoff Depth>5.84"
Flow Length=490' Tc=10.3 min CN=78 Runoff=72.97 cfs 6.047 af

Subcatchment1PRE: WATERSHED 1 PRE Runoff Area=690,940 sf 16.39% Impervious Runoff Depth>6.20"
Flow Length=490' Tc=12.4 min CN=81 Runoff=92.16 cfs 8.198 af

Subcatchment2A POST: WATERSHED Runoff Area=193,390 sf 49.12% Impervious Runoff Depth>6.81"
Flow Length=395' Tc=7.4 min CN=86 Runoff=32.31 cfs 2.519 af

Subcatchment2B POST: WATERSHED Runoff Area=635,992 sf 67.64% Impervious Runoff Depth>7.29"
Flow Length=300' Tc=10.8 min CN=90 Runoff=99.54 cfs 8.865 af

Subcatchment2PRE: WATERSHED 2 PRE Runoff Area=829,559 sf 52.29% Impervious Runoff Depth>6.80"
Flow Length=630' Tc=12.6 min CN=86 Runoff=118.12 cfs 10.797 af

Reach DP1: DP1 Inflow=81.05 cfs 6.768 af
Outflow=81.05 cfs 6.768 af

Reach DP2: DP2 Inflow=109.68 cfs 11.021 af
Outflow=109.68 cfs 11.021 af

Pond IB1: INFILTRATION BASIN 1 Peak Elev=505.74' Storage=23,889 cf Inflow=28.03 cfs 1.945 af
Discarded=2.32 cfs 1.223 af Primary=8.60 cfs 0.722 af Secondary=0.00 cfs 0.000 af Outflow=10.92 cfs 1.945 af

Pond SB1: SEDIMENTATION BASIN 1 Peak Elev=505.75' Storage=4,534 cf Inflow=26.92 cfs 2.025 af
Outflow=28.03 cfs 1.945 af

Pond SWB2: STORMWATER BASIN 2 Peak Elev=445.60' Storage=38,909 cf Inflow=32.31 cfs 2.519 af
Primary=11.17 cfs 2.145 af Secondary=0.72 cfs 0.010 af Outflow=11.89 cfs 2.155 af

Total Runoff Area = 69.808 ac Runoff Volume = 38.452 af Average Runoff Depth = 6.61"
58.05% Pervious = 40.526 ac 41.95% Impervious = 29.281 ac


Summary for Subcatchment 1APOST: WATERSHED 1A POST

Runoff = 26.92 cfs @ 12.08 hrs, Volume= 2.025 af, Depth> 7.05"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type III 24-hr 100 YR Rainfall=8.50"

Area (sf)	CN	Description
90,000	98	Paved parking, HSG C
60,150	74	>75% Grass cover, Good, HSG C
150,150	88	Weighted Average
60,150		40.06% Pervious Area
90,000		59.94% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
0.7	100	0.0900	2.53		Sheet Flow, Sheet Flow Smooth surfaces n= 0.011 P2= 3.25"
2.7	460	0.0200	2.87		Shallow Concentrated Flow, Shallow Flow to SW Basin Paved Kv= 20.3 fps
3.4	560	Total, Increased to minimum Tc = 6.0 min			

Subcatchment 1APOST: WATERSHED 1A POST


Summary for Subcatchment 1BPOST: WATERSHED 1B POST

Runoff = 72.97 cfs @ 12.14 hrs, Volume= 6.047 af, Depth> 5.84"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type III 24-hr 100 YR Rainfall=8.50"

Area (sf)	CN	Description
113,266	98	Water Surface, HSG C
277,724	74	>75% Grass cover, Good, HSG C
149,800	70	Woods, Good, HSG C
540,790	78	Weighted Average
427,524		79.06% Pervious Area
113,266		20.94% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.4	100	0.0400	0.23		Sheet Flow, Sheet Flow Grass: Short n= 0.150 P2= 3.25"
1.3	205	0.1500	2.71		Shallow Concentrated Flow, Shallow Flow to Woods Short Grass Pasture Kv= 7.0 fps
1.6	185	0.1400	1.87		Shallow Concentrated Flow, Shallow Flow Woods to Wetland Woodland Kv= 5.0 fps
10.3	490	Total			

Subcatchment 1BPOST: WATERSHED 1B POST


Summary for Subcatchment 1PRE: WATERSHED 1 PRE

Runoff = 92.16 cfs @ 12.17 hrs, Volume= 8.198 af, Depth> 6.20"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type III 24-hr 100 YR Rainfall=8.50"

Area (sf)	CN	Description
113,266	98	Water Surface, HSG C
374,041	82	Row crops, SR + CR, Good, HSG C
203,633	70	Woods, Good, HSG C
690,940	81	Weighted Average
577,674		83.61% Pervious Area
113,266		16.39% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
8.1	100	0.0400	0.20		Sheet Flow, Sheet Flow Cultivated: Residue>20% n= 0.170 P2= 3.25"
1.0	205	0.1500	3.49		Shallow Concentrated Flow, Shallow Flow to Woods Cultivated Straight Rows Kv= 9.0 fps
3.3	185	0.1400	0.94		Shallow Concentrated Flow, Shallow Flow Woods to Wetland Forest w/Heavy Litter Kv= 2.5 fps
12.4	490	Total			

Subcatchment 1PRE: WATERSHED 1 PRE

Summary for Subcatchment 2A POST: WATERSHED 2A POST


Runoff = 32.31 cfs @ 12.10 hrs, Volume= 2.519 af, Depth> 6.81"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type III 24-hr 100 YR Rainfall=8.50"

Area (sf)	CN	Description
98,390	74	>75% Grass cover, Good, HSG C
95,000	98	Paved parking, HSG C
193,390	86	Weighted Average
98,390		50.88% Pervious Area
95,000		49.12% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.6	100	0.0800	0.30		Sheet Flow, Sheet Flow Grass: Short n= 0.150 P2= 3.25"
0.4	60	0.1500	2.71		Shallow Concentrated Flow, Shallow Flow to Pavement Short Grass Pasture Kv= 7.0 fps
1.4	235	0.0200	2.87		Shallow Concentrated Flow, Shallow Flow Pavement to Catchbasin Paved Kv= 20.3 fps
7.4	395	Total			

Subcatchment 2A POST: WATERSHED 2A POST




Summary for Subcatchment 2B POST: WATERSHED 2B POST

Runoff = 99.54 cfs @ 12.14 hrs, Volume= 8.865 af, Depth> 7.29"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type III 24-hr 100 YR Rainfall=8.50"

Area (sf)	CN	Description
205,792	74	>75% Grass cover, Good, HSG C
430,200	98	Water Surface, HSG C
635,992	90	Weighted Average
205,792		32.36% Pervious Area
430,200		67.64% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
8.9	100	0.0250	0.19		Sheet Flow, Sheet Flow
					Grass: Short n= 0.150 P2= 3.25"
1.9	200	0.0650	1.78		Shallow Concentrated Flow, Shallow Flow to Wetland
					Short Grass Pasture Kv= 7.0 fps
10.8	300	Total			

Subcatchment 2B POST: WATERSHED 2B POST


Summary for Subcatchment 2PRE: WATERSHED 2 PRE

Runoff = 118.12 cfs @ 12.17 hrs, Volume= 10.797 af, Depth> 6.80"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type III 24-hr 100 YR Rainfall=8.50"

Area (sf)	CN	Description
187,773	74	>75% Grass cover, Good, HSG C
433,755	98	Water Surface, HSG C
208,031	70	Woods, Good, HSG C
829,559	86	Weighted Average
395,804		47.71% Pervious Area
433,755		52.29% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.3	100	0.0600	0.27		Sheet Flow, Sheet Flow
					Grass: Short n= 0.150 P2= 3.25"
6.3	530	0.0400	1.40		Shallow Concentrated Flow, Shallow Flow to Wetland
					Short Grass Pasture Kv= 7.0 fps
12.6	630	Total			

Subcatchment 2PRE: WATERSHED 2 PRE


Summary for Reach DP1: DP1

Inflow Area = 15.862 ac, 29.42% Impervious, Inflow Depth > 5.12" for 100 YR event
Inflow = 81.05 cfs @ 12.14 hrs, Volume= 6.768 af
Outflow = 81.05 cfs @ 12.14 hrs, Volume= 6.768 af, Atten= 0%, Lag= 0.0 min

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Reach DP1: DP1

Hydrograph




Summary for Reach DP2: DP2

Inflow Area = 19.040 ac, 63.32% Impervious, Inflow Depth > 6.95" for 100 YR event
Inflow = 109.68 cfs @ 12.15 hrs, Volume= 11.021 af
Outflow = 109.68 cfs @ 12.15 hrs, Volume= 11.021 af, Atten= 0%, Lag= 0.0 min

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Reach DP2: DP2

Hydrograph



Summary for Pond IB1: INFILTRATION BASIN 1

Inflow Area = 3.447 ac, 59.94% Impervious, Inflow Depth > 6.77" for 100 YR event
 Inflow = 28.03 cfs @ 12.08 hrs, Volume= 1.945 af
 Outflow = 10.92 cfs @ 12.30 hrs, Volume= 1.945 af, Atten= 61%, Lag= 12.9 min
 Discarded = 2.32 cfs @ 12.30 hrs, Volume= 1.223 af
 Primary = 8.60 cfs @ 12.30 hrs, Volume= 0.722 af
 Secondary = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 505.74' @ 12.30 hrs Surf.Area= 9,302 sf Storage= 23,889 cf
 Flood Elev= 506.50' Surf.Area= 10,500 sf Storage= 31,452 cf

Plug-Flow detention time= (not calculated: outflow precedes inflow)
 Center-of-Mass det. time= 65.1 min (863.6 - 798.5)

Volume	Invert	Avail.Storage	Storage Description		
#1	502.00'	31,452 cf	Custom Stage Data (Irregular) Listed below (Recalc)		
Elevation (feet)	Surf.Area (sq-ft)	Perim. (feet)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)	Wet.Area (sq-ft)
502.00	4,965	280.0	0	0	4,965
504.00	5,850	300.0	10,803	10,803	6,055
506.00	9,880	450.0	15,555	26,358	15,039
506.50	10,500	465.0	5,094	31,452	16,155

Device	Routing	Invert	Outlet Devices
#1	Primary	503.00'	15.0" Round Culvert L= 460.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 503.00' / 496.00' S= 0.0152 ' / Cc= 0.900 n= 0.012, Flow Area= 1.23 sf
#2	Discarded	502.00'	5.000 in/hr Exfiltration over Surface area Conductivity to Groundwater Elevation = 500.00'
#3	Device 1	504.00'	Custom Weir/Orifice X 4.00, Cv= 2.62 (C= 3.28) Head (feet) 0.00 1.50 Width (feet) 2.00 2.00
#4	Device 1	505.50'	30.0" x 48.0" Horiz. Orifice/Grate C= 0.600 in 42.0" x 60.0" Grate (57% open area) Limited to weir flow at low heads
#5	Secondary	506.30'	15.0' long x 5.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 5.00 5.50 Coef. (English) 2.34 2.50 2.70 2.68 2.68 2.66 2.65 2.65 2.65 2.65 2.67 2.66 2.68 2.70 2.74 2.79 2.88

Discarded OutFlow Max=2.32 cfs @ 12.30 hrs HW=505.74' (Free Discharge)

↳ **2=Exfiltration** (Controls 2.32 cfs)

Primary OutFlow Max=8.60 cfs @ 12.30 hrs HW=505.74' TW=0.00' (Dynamic Tailwater)

↳ **1=Culvert** (Inlet Controls 8.60 cfs @ 7.01 fps)


↳ **3=Custom Weir/Orifice** (Passes < 57.13 cfs potential flow)

↳ **4=Orifice/Grate** (Passes < 5.07 cfs potential flow)

Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=502.00' TW=0.00' (Dynamic Tailwater)

↳ **5=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)

Pond IB1: INFILTRATION BASIN 1



Summary for Pond SB1: SEDIMENTATION BASIN 1

Inflow Area = 3.447 ac, 59.94% Impervious, Inflow Depth > 7.05" for 100 YR event
 Inflow = 26.92 cfs @ 12.08 hrs, Volume= 2.025 af
 Outflow = 28.03 cfs @ 12.08 hrs, Volume= 1.945 af, Atten= 0%, Lag= 0.0 min
 Primary = 28.03 cfs @ 12.08 hrs, Volume= 1.945 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 505.75' @ 12.30 hrs Surf.Area= 2,340 sf Storage= 4,534 cf
 Flood Elev= 506.50' Surf.Area= 2,340 sf Storage= 4,534 cf


Plug-Flow detention time= 42.0 min calculated for 1.945 af (96% of inflow)
 Center-of-Mass det. time= 18.9 min (798.5 - 779.6)

Volume	Invert	Avail.Storage	Storage Description
#1	501.00'	4,534 cf	Custom Stage Data (Irregular) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Perim. (feet)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)	Wet.Area (sq-ft)
501.00	800	130.0	0	0	800
502.00	1,240	160.0	1,012	1,012	1,507
504.00	2,340	220.0	3,522	4,534	3,361

Device	Routing	Invert	Outlet Devices
#1	Primary	503.50'	15.0' long x 5.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 5.00 5.50 Coef. (English) 2.34 2.50 2.70 2.68 2.68 2.66 2.65 2.65 2.65 2.65 2.67 2.66 2.68 2.70 2.74 2.79 2.88

Primary OutFlow Max=0.00 cfs @ 12.08 hrs HW=505.08' TW=505.09' (Dynamic Tailwater)
 ↑1=Broad-Crested Rectangular Weir (Controls 0.00 cfs)

Pond SB1: SEDIMENTATION BASIN 1

Summary for Pond SWB2: STORMWATER BASIN 2

Inflow Area = 4.440 ac, 49.12% Impervious, Inflow Depth > 6.81" for 100 YR event
 Inflow = 32.31 cfs @ 12.10 hrs, Volume= 2.519 af
 Outflow = 11.89 cfs @ 12.38 hrs, Volume= 2.155 af, Atten= 63%, Lag= 16.5 min
 Primary = 11.17 cfs @ 12.38 hrs, Volume= 2.145 af
 Secondary = 0.72 cfs @ 12.38 hrs, Volume= 0.010 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 445.60' @ 12.38 hrs Surf.Area= 13,393 sf Storage= 38,909 cf
 Flood Elev= 446.00' Surf.Area= 14,315 sf Storage= 44,478 cf

Plug-Flow detention time= 117.6 min calculated for 2.155 af (86% of inflow)
 Center-of-Mass det. time= 55.9 min (842.2 - 786.3)

Volume	Invert	Avail.Storage	Storage Description		
#1	441.50'	44,478 cf	Custom Stage Data (Irregular) Listed below (Recalc)		
Elevation (feet)	Surf.Area (sq-ft)	Perim. (feet)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)	Wet.Area (sq-ft)
441.50	6,320	601.0	0	0	6,320
444.00	10,030	660.0	20,260	20,260	12,447
446.00	14,315	725.0	24,218	44,478	19,743


Device	Routing	Invert	Outlet Devices
#1	Primary	442.50'	18.0" Round Culvert L= 180.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 442.50' / 441.60' S= 0.0050 '/' Cc= 0.900 n= 0.012, Flow Area= 1.77 sf
#2	Primary	443.00'	3.0" Vert. Orifice/Grate C= 0.600
#3	Device 1	443.50'	Custom Weir/Orifice X 4.00, Cv= 2.62 (C= 3.28) Head (feet) 0.00 2.00 Width (feet) 1.50 1.50
#4	Device 1	445.50'	30.0" x 48.0" Horiz. Orifice/Grate C= 0.600 in 42.0" x 60.0" Grate (57% open area) Limited to weir flow at low heads
#5	Secondary	445.50'	10.0' long x 5.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 5.00 5.50 Coef. (English) 2.34 2.50 2.70 2.68 2.68 2.66 2.65 2.65 2.65 2.65 2.67 2.66 2.68 2.70 2.74 2.79 2.88

Primary OutFlow Max=11.17 cfs @ 12.38 hrs HW=445.60' TW=0.00' (Dynamic Tailwater)

1=Culvert (Barrel Controls 10.80 cfs @ 6.11 fps)
 3=Custom Weir/Orifice (Passes < 59.11 cfs potential flow)
 4=Orifice/Grate (Passes < 1.30 cfs potential flow)
 2=Orifice/Grate (Orifice Controls 0.37 cfs @ 7.57 fps)

Secondary OutFlow Max=0.72 cfs @ 12.38 hrs HW=445.60' TW=0.00' (Dynamic Tailwater)

5=Broad-Crested Rectangular Weir (Weir Controls 0.72 cfs @ 0.73 fps)

Pond SWB2: STORMWATER BASIN 2

APPENDIX C

ATTACHMENT 1

Construction Stormwater Compliance Inspection Report

Project Name and Location:	Date:	Page 1 of 2
	Permit # (if any): NYR	
	Municipality:	County:
On-site Representative(s) and contact information:	Weather Conditions:	
Name and Address of SPDES Permittee/Title/Phone/Fax Numbers: Contacted: Yes <input type="checkbox"/> No <input type="checkbox"/>		

INSPECTION CHECKLIST

SPDES Authority

Yes No N/A

1. ☐ ☐ ☐ Is a copy of the NOI posted at the construction site for public viewing?
2. ☐ ☐ ☐ Is an up-to-date copy of the signed SWPPP retained at the construction site?
3. ☐ ☐ ☐ Is a copy of the SPDES General Permit retained at the construction site?

Law, rule or permit citation

SWPPP Content

Yes No N/A

4. ☐ ☐ ☐ Does the SWPPP describe and identify the erosion & sediment control measures to be employed?
5. ☐ ☐ ☐ Does the SWPPP provide a maintenance schedule for the erosion & sediment control measures?
6. ☐ ☐ ☐ Does the SWPPP describe and identify the post-construction SW control measures to be employed?
7. ☐ ☐ ☐ Does the SWPPP identify the contractor(s) and subcontractor(s) responsible for each measure?
8. ☐ ☐ ☐ Does the SWPPP include all the necessary 'CONTRACTOR CERTIFICATION' statements?
9. ☐ ☐ ☐ Is the SWPPP signed/certified by the permittee?

Law, rule or permit citation

Recordkeeping

Yes No N/A

10. ☐ ☐ ☐ Are inspections performed as required by the permit (every 7 days and after 1/2" rain event)?
11. ☐ ☐ ☐ Are the site inspections performed by a qualified professional?
12. ☐ ☐ ☐ Are all required reports properly signed/certified?
13. ☐ ☐ ☐ Does the SWPPP include copies of the monthly/quarterly written summaries of compliance status?

Law, rule or permit citation

Visual Observations

Yes No N/A

14. ☐ ☐ ☐ Are all erosion and sediment control measures installed/constructed?
15. ☐ ☐ ☐ Are all erosion and sediment control measures maintained properly?
16. ☐ ☐ ☐ Have all disturbances of 5 acres or more been approved prior to the disturbance?
17. ☐ ☐ ☐ Are stabilization measures initiated in inactive areas?
18. ☐ ☐ ☐ Are permanent stormwater control measures implemented?
19. ☐ ☐ ☐ Was there a discharge into the receiving water on the day of inspection?
20. ☐ ☐ ☐ Are receiving waters free of there evidence of turbidity, sedimentation, or oil ? (If no , complete Page 2)

Law, rule or permit citation

Overall Inspection Rating: <input type="checkbox"/> Satisfactory <input type="checkbox"/> Marginal <input type="checkbox"/> Unsatisfactory	
Name/Agency of Lead Inspector:	Signature of Lead Inspector:
Names/Agencies of Other Inspectors:	

Water Quality Observations

Describe the discharge(s) [source(s), impact on receiving water(s), etc.] _____

Describe the quality of the receiving water(s) both upstream and downstream of the discharge_____

Describe any other water quality standards or permit violations _____

Additional Comments: _____

This image shows a single sheet of white paper with horizontal blue or grey ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.

☐ Photographs attached

APPENDIX H

STATE POLLUTANT DISCHARGE ELIMINATION SYSTEM FOR CONSTRUCTION ACTIVITIES CONSTRUCTION SITE LOG BOOK

Table of Contents

- I. Pre-Construction Meeting Documents
 - a. Preamble to Site Assessment and Inspections
 - b. Operator's Certification
 - c. Qualified Professional's Credentials & Certification
 - d. Pre-Construction Site Assessment Checklist
- II. Construction Duration Inspections
 - a. Directions
 - b. Modification to the SWPPP
- III. Monthly Summary Reports
- IV. Monitoring, Reporting, and Three-Month Status Reports
 - a. Operator's Compliance Response Form

Properly completing forms such as those contained in Appendix H meet the inspection requirement of NYS-DEC SPDES GP for Construction Activities. Completed forms shall be kept on site at all times and made available to authorities upon request.

I. PRE-CONSTRUCTION MEETING DOCUMENTS

Project Name _____
Permit No. _____ **Date of Authorization** _____
Name of Operator _____
Prime Contractor _____

a. Preamble to Site Assessment and Inspections

The Following Information To Be Read By All Person's Involved in The Construction of Stormwater Related Activities:

The Operator agrees to have a qualified professional¹ conduct an assessment of the site prior to the commencement of construction² and certify in this inspection report that the appropriate erosion and sediment controls described in the SWPPP have been adequately installed or implemented to ensure overall preparedness of the site for the commencement of construction.

Prior to the commencement of construction, the Operator shall certify in this site logbook that the SWPPP has been prepared in accordance with the State's standards and meets all Federal, State and local erosion and sediment control requirements.

When construction starts, site inspections shall be conducted by the qualified professional at least every 7 calendar days and within 24 hours of the end of a storm event of 0.5 inches or greater (Construction Duration Inspections). The Operator shall maintain a record of all inspection reports in this site logbook. The site logbook shall be maintained on site and be made available to the permitting authorities upon request. The Operator shall post at the site, in a publicly accessible location, a summary of the site inspection activities on a monthly basis (Monthly Summary Report).

The operator shall also prepare a written summary of compliance with this general permit at a minimum frequency of every three months (Operator's Compliance Response Form), while coverage exists. The summary should address the status of achieving each component of the SWPPP.

Prior to filing the Notice of Termination or the end of permit term, the Operator shall have a qualified professional perform a final site inspection. The qualified professional shall certify that the site has undergone final stabilization³ using either vegetative or structural stabilization methods and that all temporary erosion and sediment controls (such as silt fencing) not needed for long-term erosion control have been removed. In addition, the Operator must identify and certify that all permanent structures described in the SWPPP have been constructed and provide the owner(s) with an operation and maintenance plan that ensures the structure(s) continuously functions as designed.

1 "Qualified Professional means a person knowledgeable in the principles and practice of erosion and sediment controls, such as a Certified Professional in Erosion and Sediment Control (CPESC), soil scientist, licensed engineer or someone working under the direction and supervision of a licensed engineer (person must have experience in the principles and practices of erosion and sediment control).

2 "Commencement of construction" means the initial removal of vegetation and disturbance of soils associated with clearing, grading or excavating activities or other construction activities.

3 "Final stabilization" means that all soil-disturbing activities at the site have been completed and a uniform, perennial vegetative cover with a density of eighty (80) percent has been established or equivalent stabilization measures (such as the use of mulches or geotextiles) have been employed on all unpaved areas and areas not covered by permanent structures.

b. Operators Certification

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. Further, I hereby certify that the SWPPP meets all Federal, State, and local erosion and sediment control requirements. I am aware that false statements made herein are punishable as a class A misdemeanor pursuant to Section 210.45 of the Penal Law.

Name (please print): _____

Title _____ **Date:** _____

Address: _____

Phone: _____ **Email:** _____

Signature: _____

c. Qualified Professional's Credentials & Certification

"I hereby certify that I meet the criteria set forth in the General Permit to conduct site inspections for this project and that the appropriate erosion and sediment controls described in the SWPPP and as described in the following Pre-construction Site Assessment Checklist have been adequately installed or implemented, ensuring the overall preparedness of this site for the commencement of construction."

Name (please print): _____

Title _____ **Date:** _____

Address: _____

Phone: _____ **Email:** _____

Signature: _____

d. Pre-construction Site Assessment Checklist

(NOTE: Provide comments below as necessary)

1. Notice of Intent, SWPPP, and Contractors Certification:

Yes No NA

- ☐ ☐ ☐ Has a Notice of Intent been filed with the NYS Department of Conservation?
- ☐ ☐ ☐ Is the SWPPP on-site? Where? _____
- ☐ ☐ ☐ Is the Plan current? What is the latest revision date? _____
- ☐ ☐ ☐ Is a copy of the NOI (with brief description) onsite? Where? _____
- ☐ ☐ ☐ Have all contractors involved with stormwater related activities signed a contractor's certification?

2. Resource Protection

Yes No NA

- ☐ ☐ ☐ Are construction limits clearly flagged or fenced?
- ☐ ☐ ☐ Important trees and associated rooting zones, on-site septic system absorption fields, existing vegetated areas suitable for filter strips, especially in perimeter areas, have been flagged for protection.
- ☐ ☐ ☐ Creek crossings installed prior to land-disturbing activity, including clearing and blasting.

3. Surface Water Protection

Yes No NA

- ☐ ☐ ☐ Clean stormwater runoff has been diverted from areas to be disturbed.
- ☐ ☐ ☐ Bodies of water located either on site or in the vicinity of the site have been identified and protected.
- ☐ ☐ ☐ Appropriate practices to protect on-site or downstream surface water are installed.
- ☐ ☐ ☐ Are clearing and grading operations divided into areas <5 acres?

4. Stabilized Construction Entrance

Yes No NA

- ☐ ☐ ☐ A temporary construction entrance to capture mud and debris from construction vehicles before they enter the public highway has been installed.
- ☐ ☐ ☐ Other access areas (entrances, construction routes, equipment parking areas) are stabilized immediately as work takes place with gravel or other cover.
- ☐ ☐ ☐ Sediment tracked onto public streets is removed or cleaned on a regular basis.

5. Perimeter Sediment Controls

Yes No NA

- ☐ ☐ ☐ Silt fence material and installation comply with the standard drawing and specifications.
- ☐ ☐ ☐ Silt fences are installed at appropriate spacing intervals
- ☐ ☐ ☐ Sediment/detention basin was installed as first land disturbing activity.
- ☐ ☐ ☐ Sediment traps and barriers are installed.

6. Pollution Prevention for Waste and Hazardous Materials

Yes No NA

- ☐ ☐ ☐ The Operator or designated representative has been assigned to implement the spill prevention avoidance and response plan.
- ☐ ☐ ☐ The plan is contained in the SWPPP on page _____
- ☐ ☐ ☐ Appropriate materials to control spills are onsite. Where? _____

II. CONSTRUCTION DURATION INSPECTIONS

a. Directions:

Inspection Forms will be filled out during the entire construction phase of the project.

Required Elements:

- (1) On a site map, indicate the extent of all disturbed site areas and drainage pathways. Indicate site areas that are expected to undergo initial disturbance or significant site work within the next 14-day period;
- (2) Indicate on a site map all areas of the site that have undergone temporary or permanent stabilization;
- (3) Indicate all disturbed site areas that have not undergone active site work during the previous 14-day period;
- (4) Inspect all sediment control practices and record the approximate degree of sediment accumulation as a percentage of sediment storage volume (for example, 10 percent, 20 percent, 50 percent);
- (5) Inspect all erosion and sediment control practices and record all maintenance requirements such as verifying the integrity of barrier or diversion systems (earthen berms or silt fencing) and containment systems (sediment basins and sediment traps). Identify any evidence of rill or gully erosion occurring on slopes and any loss of stabilizing vegetation or seeding/mulching. Document any excessive deposition of sediment or ponding water along barrier or diversion systems. Record the depth of sediment within containment structures, any erosion near outlet and overflow structures, and verify the ability of rock filters around perforated riser pipes to pass water; and
- (6) Immediately report to the Operator any deficiencies that are identified with the implementation of the SWPPP.

SITE PLAN/SKETCH

Inspector (print name)

Date of Inspection

Qualified Professional (print name)

Qualified Professional Signature

The above signed acknowledges that, to the best of his/her knowledge, all information provided on the forms is accurate and complete.

Maintaining Water Quality**Yes No NA**

- ☐ ☐ ☐ Is there an increase in turbidity causing a substantial visible contrast to natural conditions?
- ☐ ☐ ☐ Is there residue from oil and floating substances, visible oil film, or globules or grease?
- ☐ ☐ ☐ All disturbance is within the limits of the approved plans.
- ☐ ☐ ☐ Have receiving lake/bay, stream, and/or wetland been impacted by silt from project?

Housekeeping

1. General Site Conditions

Yes No NA

- ☐ ☐ ☐ Is construction site litter and debris appropriately managed?
- ☐ ☐ ☐ Are facilities and equipment necessary for implementation of erosion and sediment control in working order and/or properly maintained?
- ☐ ☐ ☐ Is construction impacting the adjacent property?
- ☐ ☐ ☐ Is dust adequately controlled?

2. Temporary Stream Crossing

Yes No NA

- ☐ ☐ ☐ Maximum diameter pipes necessary to span creek without dredging are installed.
- ☐ ☐ ☐ Installed non-woven geotextile fabric beneath approaches.
- ☐ ☐ ☐ Is fill composed of aggregate (no earth or soil)?
- ☐ ☐ ☐ Rock on approaches is clean enough to remove mud from vehicles & prevent sediment from entering stream during high flow.

Runoff Control Practices

1. Excavation Dewatering

Yes No NA

- ☐ ☐ ☐ Upstream and downstream berms (sandbags, inflatable dams, etc.) are installed per plan.
- ☐ ☐ ☐ Clean water from upstream pool is being pumped to the downstream pool.
- ☐ ☐ ☐ Sediment laden water from work area is being discharged to a silt-trapping device.
- ☐ ☐ ☐ Constructed upstream berm with one-foot minimum freeboard.

2. Level Spreader

Yes No NA

- ☐ ☐ ☐ Installed per plan.
- ☐ ☐ ☐ Constructed on undisturbed soil, not on fill, receiving only clear, non-sediment laden flow.
- ☐ ☐ ☐ Flow sheets out of level spreader without erosion on downstream edge.

3. Interceptor Dikes and Swales

Yes No NA

- ☐ ☐ ☐ Installed per plan with minimum side slopes 2H:1V or flatter.
- ☐ ☐ ☐ Stabilized by geotextile fabric, seed, or mulch with no erosion occurring.
- ☐ ☐ ☐ Sediment-laden runoff directed to sediment trapping structure

Runoff Control Practices (continued)**4. Stone Check Dam****Yes No NA**

- ☐ ☐ ☐ Is channel stable? (flow is not eroding soil underneath or around the structure).
- ☐ ☐ ☐ Check is in good condition (rocks in place and no permanent pools behind the structure).
- ☐ ☐ ☐ Has accumulated sediment been removed?.

5. Rock Outlet Protection**Yes No NA**

- ☐ ☐ ☐ Installed per plan.
- ☐ ☐ ☐ Installed concurrently with pipe installation.

Soil Stabilization**1. Topsoil and Spoil Stockpiles****Yes No NA**

- ☐ ☐ ☐ Stockpiles are stabilized with vegetation and/or mulch.
- ☐ ☐ ☐ Sediment control is installed at the toe of the slope.

2. Revegetation**Yes No NA**

- ☐ ☐ ☐ Temporary seedings and mulch have been applied to idle areas.
- ☐ ☐ ☐ 4 inches minimum of topsoil has been applied under permanent seedings

Sediment Control Practices**1. Stabilized Construction Entrance****Yes No NA**

- ☐ ☐ ☐ Stone is clean enough to effectively remove mud from vehicles.
- ☐ ☐ ☐ Installed per standards and specifications?
- ☐ ☐ ☐ Does all traffic use the stabilized entrance to enter and leave site?
- ☐ ☐ ☐ Is adequate drainage provided to prevent ponding at entrance?

2. Silt Fence**Yes No NA**

- ☐ ☐ ☐ Installed on Contour, 10 feet from toe of slope (not across conveyance channels).
- ☐ ☐ ☐ Joints constructed by wrapping the two ends together for continuous support.
- ☐ ☐ ☐ Fabric buried 6 inches minimum.
- ☐ ☐ ☐ Posts are stable, fabric is tight and without rips or frayed areas.
- Sediment accumulation is ____% of design capacity.

Sediment Control Practices (continued)**3. Storm Drain Inlet Protection (Use for Stone & Block; Filter Fabric; Curb; or, Excavated practices)****Yes No NA**

- ☐ ☐ ☐ Installed concrete blocks lengthwise so open ends face outward, not upward.
- ☐ ☐ ☐ Placed wire screen between No. 3 crushed stone and concrete blocks.
- ☐ ☐ ☐ Drainage area is 1 acre or less.
- ☐ ☐ ☐ Excavated area is 900 cubic feet.
- ☐ ☐ ☐ Excavated side slopes should be 2:1.
- ☐ ☐ ☐ 2" x 4" frame is constructed and structurally sound.
- ☐ ☐ ☐ Posts 3-foot maximum spacing between posts.
- ☐ ☐ ☐ Fabric is embedded 1 to 1.5 feet below ground and secured to frame/posts with staples at max 8-inch spacing.
- ☐ ☐ ☐ Posts are stable, fabric is tight and without rips or frayed areas.
- Sediment accumulation ____% of design capacity.

4. Temporary Sediment Trap**Yes No NA**

- ☐ ☐ ☐ Outlet structure is constructed per the approved plan or drawing.
- ☐ ☐ ☐ Geotextile fabric has been placed beneath rock fill.
- Sediment accumulation is ____% of design capacity.

5. Temporary Sediment Basin**Yes No NA**

- ☐ ☐ ☐ Basin and outlet structure constructed per the approved plan.
- ☐ ☐ ☐ Basin side slopes are stabilized with seed/mulch.
- ☐ ☐ ☐ Drainage structure flushed and basin surface restored upon removal of sediment basin facility.
- Sediment accumulation is ____% of design capacity.

Note: Not all erosion and sediment control practices are included in this listing. Add additional pages to this list as required by site specific design.

Construction inspection checklists for post-development stormwater management practices can be found in Appendix F of the New York Stormwater Management Design Manual.

CONSTRUCTION DURATION INSPECTIONS

b. Modifications to the SWPPP (To be completed as described below)

The Operator shall amend the SWPPP whenever:

1. There is a significant change in design, construction, operation, or maintenance which may have a significant effect on the potential for the discharge of pollutants to the waters of the United States and which has not otherwise been addressed in the SWPPP; or
2. The SWPPP proves to be ineffective in:
 - a. Eliminating or significantly minimizing pollutants from sources identified in the SWPPP and as required by this permit; or
 - b. Achieving the general objectives of controlling pollutants in stormwater discharges from permitted construction activity; and
3. Additionally, the SWPPP shall be amended to identify any new contractor or subcontractor that will implement any measure of the SWPPP.

Modification & Reason:[illegible]

III. Monthly Summary of Site Inspection Activities

Name of Permitted Facility:	Today's Date:	Reporting Month:
Location:	Permit Identification #:	
Name and Telephone Number of Site Inspector:		

[illegible]

Owner/Operator Certification:

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that false statements made herein are punishable as a class A misdemeanor pursuant to Section 210.45 of the Penal Law."

Signature of Permittee or Duly Authorized Representative


Name of Permittee or Duly Authorized Representative

Date _____

Duly authorized representatives must have written authorization, submitted to DEC, to sign any permit documents.

APPENDIX D

NOTICE OF INTENT



New York State Department of Environmental Conservation

Division of Water

625 Broadway, 4th Floor

Albany, New York 12233-3505

NYR [] [] [] [] []
(for DEC use only)

Stormwater Discharges Associated with Construction Activity Under State Pollutant Discharge Elimination System (SPDES) General Permit # GP-0-15-002

All sections must be completed unless otherwise noted. Failure to complete all items may result in this form being returned to you, thereby delaying your coverage under this General Permit. Applicants must read and understand the conditions of the permit and prepare a Stormwater Pollution Prevention Plan prior to submitting this NOI. Applicants are responsible for identifying and obtaining other DEC permits that may be required.

- IMPORTANT -

RETURN THIS FORM TO THE ADDRESS ABOVE

OWNER/OPERATOR MUST SIGN FORM

Owner/Operator Information

Owner/Operator (Company Name/Private Owner Name/Municipality Name)

[illegible]

Owner/Operator Contact Person Last Name (NOT CONSULTANT)

[illegible]

Owner/Operator Contact Person First Name

[illegible]

Owner/Operator Mailing Address

[illegible]

City

[illegible]

State

--	--

Zip

--	--	--	--	--	--	--	--	--

Phone (Owner/Operator)

			-				-			
--	--	--	---	--	--	--	---	--	--	--

Fax (Owner/Operator)

			-				-			
--	--	--	---	--	--	--	---	--	--	--

Email (Owner/Operator)

[illegible][illegible]

FED TAX ID

		-							
--	--	---	--	--	--	--	--	--	--

(not required for individuals)

Project Site Information

Project/Site Name

[illegible]

Street Address (NOT P.O. BOX)

[illegible]

Side of Street

☐ North ☐ South ☐ East ☐ West

City/Town/Village (THAT ISSUES BUILDING PERMIT)

[illegible]

State

Zip

--	--

--	--	--	--	--

—

--	--	--	--

County

[illegible]DEC Region

--	--

Name of Nearest Cross Street

[illegible]

Distance to Nearest Cross Street (Feet)

--	--	--	--	--

Project In Relation to Cross Street

☐ North ☐ South ☐ East ☐ West

Tax Map Numbers

Section-Block-Parcel

[illegible]

Tax Map Numbers

[illegible]

1. Provide the Geographic Coordinates for the project site in NYTM Units. To do this you **must** go to the NYSDEC Stormwater Interactive Map on the DEC website at:

www.dec.ny.gov/imsmaps/stormwater/viewer.htm

Zoom into your Project Location such that you can accurately click on the centroid of your site. Once you have located your project site, go to the tool boxes on the top and choose "i"(identify). Then click on the center of your site and a new window containing the X, Y coordinates in UTM will pop up. Transcribe these coordinates into the boxes below. For problems with the interactive map use the help function.

X Coordinates (Easting)

--	--	--	--	--	--

Y Coordinates (Northing)

--	--	--	--	--	--	--

2. What is the nature of this construction project?

- New Construction

- Redevelopment with increase in impervious area

- Redevelopment with no increase in impervious area

Pre-Development
Existing Land Use

- [illegible]

○ SINGLE FAMILY HOME Number of Lots

- [illegible]

4. In accordance with the larger common plan of development or sale, enter the total project site area; the total area to be disturbed; existing impervious area to be disturbed (for redevelopment activities); and the future impervious area constructed within the disturbed area. (Round to the nearest tenth of an acre.)

--	--	--	--

 .

--

--	--	--	--	--	--

--	--	--	--	--	--

--	--	--	--

--

6. Indicate the percentage of each Hydrologic Soil Group(HSG) at the site.

D			%

		/			/				
--	--	---	--	--	---	--	--	--	--

		/			/				
--	--	---	--	--	---	--	--	--	--

Name _____

[illegible]

- ☐ Wetland / State Jurisdiction On Site (Answer 9b)
☐ Wetland / State Jurisdiction Off Site
☐ Wetland / Federal Jurisdiction On Site (Answer 9b)
☐ Wetland / Federal Jurisdiction Off Site
☐ Stream / Creek On Site
☐ Stream / Creek Off Site
☐ River On Site
☐ River Off Site
☐ Lake On Site
☐ Lake Off Site
☐ Other Type On Site
☐ Other Type Off Site

- ☐ Regulatory Map
- ☐ Delineated by Consultant
- ☐ Delineated by Army Corps of Engineers
- ☐ Other (identify)

11. Is this project located in one of the Watersheds identified in Appendix C of GP-0-15-002?

12. Is the project located in one of the watershed areas associated with AA and AA-S classified waters?

If no, skip question 13.

13. Does this construction activity disturb land with no existing impervious cover and where the Soil Slope Phase is identified as an E or F on the USDA Soil Survey?

If Yes, what is the acreage to be disturbed?

--	--	--	--	--	--

15. Does the site runoff enter a separate storm sewer system (including roadside drains, swales, ditches, culverts, etc)? ☐ Yes ☐ No ☐ Unknown

- [illegible]

17. Does any runoff from the site enter a sewer classified as a Combined Sewer? ☐ **Yes** ☐ **No** ☐ **Unknown**

18. Will future use of this site be an agricultural property as defined by the NYS Agriculture and Markets Law? ☐ Yes ☐ No

19. Is this property owned by a state authority, state agency, federal government or local government? ☐ Yes ☐ No

20. Is this a remediation project being done under a Department approved work plan? (i.e. CERCLA, RCRA, Voluntary Cleanup Agreement, etc.) ☐ **Yes** ☐ **No**

21. Has the required Erosion and Sediment Control component of the SWPPP been developed in conformance with the current NYS Standards and Specifications for Erosion and Sediment Control (aka Blue Book)? ☐ Yes ☐ No

22. Does this construction activity require the development of a SWPPP that includes the post-construction stormwater management practice component (i.e. Runoff Reduction, Water Quality and Quantity Control practices/techniques)? ☐ **Yes** ☐ **No**
- If No, skip questions 23 and 27-39.**

23. Has the post-construction stormwater management practice component of the SWPPP been developed in conformance with the current NYS Stormwater Management Design Manual? ☐ Yes ☐ No

24. The Stormwater Pollution Prevention Plan (SWPPP) was prepared by:

- ☐ Professional Engineer (P.E.)
- ☐ Soil and Water Conservation District (SWCD)
- ☐ Registered Landscape Architect (R.L.A.)
- ☐ Certified Professional in Erosion and Sediment Control (CPESC)
- ☐ Owner/Operator
- ☐ Other

[illegible]

SWPPP Preparer

[illegible]

Contact Name (Last, Space, First)

[illegible]

Mailing Address

[illegible]

City

[illegible]

State Zip

								-				
--	--	--	--	--	--	--	--	---	--	--	--	--

Phone

--	--	--	--

Fax

--	--	--	--	--	--	--

Email

[illegible][illegible]

SWPPP Preparer Certification

I hereby certify that the Stormwater Pollution Prevention Plan (SWPPP) for this project has been prepared in accordance with the terms and conditions of the GP-0-15-002. Furthermore, I understand that certifying false, incorrect or inaccurate information is a violation of this permit and the laws of the State of New York and could subject me to criminal, civil and/or administrative proceedings.

First Name

[illegible]

MI

--	--

Last Name

[illegible]

Signature

me me

Date _____

--	--	--	--

25. Has a construction sequence schedule for the planned management practices been prepared? ☐ Yes ☐ No

26. Select **all** of the erosion and sediment control practices that will be employed on the project site:

Temporary Structural

- ☐ Check Dams
- ☐ Construction Road Stabilization
- ☐ Dust Control
- ☐ Earth Dike
- ☐ Level Spreader
- ☐ Perimeter Dike/Swale
- ☐ Pipe Slope Drain
- ☐ Portable Sediment Tank
- ☐ Rock Dam
- ☐ Sediment Basin
- ☐ Sediment Traps
- ☐ Silt Fence
- ☐ Stabilized Construction Entrance
- ☐ Storm Drain Inlet Protection
- ☐ Straw/Hay Bale Dike
- ☐ Temporary Access Waterway Crossing
- ☐ Temporary Stormdrain Diversion
- ☐ Temporary Swale
- ☐ Turbidity Curtain
- ☐ Water bars

Biotechnical

- Brush Matting
- Wattling

Other

[illegible]

Vegetative Measures

- ☐ Brush Matting
- ☐ Dune Stabilization
- ☐ Grassed Waterway
- ☐ Mulching
- ☐ Protecting Vegetation
- ☐ Recreation Area Improvement
- ☐ Seeding
- ☐ Sodding
- ☐ Straw/Hay Bale Dike
- ☐ Streambank Protection
- ☐ Temporary Swale
- ☐ Topsoiling
- ☐ Vegetating Waterways

Permanent Structural

- ☐ Debris Basin
- ☐ Diversion
- ☐ Grade Stabilization Structure
- ☐ Land Grading
- ☐ Lined Waterway (Rock)
- ☐ Paved Channel (Concrete)
- ☐ Paved Flume
- ☐ Retaining Wall
- ☐ Riprap Slope Protection
- ☐ Rock Outlet Protection
- ☐ Streambank Protection

Post-construction Stormwater Management Practice (SMP) Requirements

**Important: Completion of Questions 27-39 is not required
if response to Question 22 is No.**

27. Identify all site planning practices that were used to prepare the final site plan/layout for the project.

- ☐ Preservation of Undisturbed Areas
- ☐ Preservation of Buffers
- ☐ Reduction of Clearing and Grading
- ☐ Locating Development in Less Sensitive Areas
- ☐ Roadway Reduction
- ☐ Sidewalk Reduction
- ☐ Driveway Reduction
- ☐ Cul-de-sac Reduction
- ☐ Building Footprint Reduction
- ☐ Parking Reduction

27a. Indicate which of the following soil restoration criteria was used to address the requirements in Section 5.1.6("Soil Restoration") of the Design Manual (2010 version).

- ☐ All disturbed areas will be restored in accordance with the Soil Restoration requirements in Table 5.3 of the Design Manual (see page 5-22).
- ☐ Compacted areas were considered as impervious cover when calculating the **WQv Required**, and the compacted areas were assigned a post-construction Hydrologic Soil Group (HSG) designation that is one level less permeable than existing conditions for the hydrology analysis.

28. Provide the total Water Quality Volume (WQv) required for this project (based on final site plan/layout).

Total WQv Required

. acre-feet

29. Identify the RR techniques (Area Reduction), RR techniques(Volume Reduction) and Standard SMPs with RRv Capacity in Table 1 (See Page 9) that were used to reduce the Total WQv Required(#28).

Also, provide in Table 1 the total impervious area that contributes runoff to each technique/practice selected. For the Area Reduction Techniques, provide the total contributing area (includes pervious area) and, if applicable, the total impervious area that contributes runoff to the technique/practice.

Note: Redevelopment projects shall use Tables 1 and 2 to identify the SMPs used to treat and/or reduce the WQv required. If runoff reduction techniques will not be used to reduce the required WQv, skip to question 33a after identifying the SMPs.

Table 1 - Runoff Reduction (RR) Techniques
and Standard Stormwater Management
Practices (SMPs)

RR Techniques (Area Reduction)	Total Contributing Area (acres)	Total Contributing Impervious Area(acres)
○ Conservation of Natural Areas (RR-1) ...	<input type="text"/> <input type="text"/> <input type="text"/> . <input type="text"/> <input type="text"/> <input type="text"/>	and/or <input type="text"/> <input type="text"/> <input type="text"/> . <input type="text"/> <input type="text"/> <input type="text"/>
○ Sheetflow to Riparian Buffers/Filters Strips (RR-2)	<input type="text"/> <input type="text"/> <input type="text"/> . <input type="text"/> <input type="text"/> <input type="text"/>	and/or <input type="text"/> <input type="text"/> <input type="text"/> . <input type="text"/> <input type="text"/> <input type="text"/>
○ Tree Planting/Tree Pit (RR-3)	<input type="text"/> <input type="text"/> <input type="text"/> . <input type="text"/> <input type="text"/> <input type="text"/>	and/or <input type="text"/> <input type="text"/> <input type="text"/> . <input type="text"/> <input type="text"/> <input type="text"/>
○ Disconnection of Rooftop Runoff (RR-4) ..	<input type="text"/> <input type="text"/> <input type="text"/> . <input type="text"/> <input type="text"/> <input type="text"/>	and/or <input type="text"/> <input type="text"/> <input type="text"/> . <input type="text"/> <input type="text"/> <input type="text"/>
RR Techniques (Volume Reduction)		
○ Vegetated Swale (RR-5)	<input type="text"/> <input type="text"/> <input type="text"/>	. <input type="text"/> <input type="text"/> <input type="text"/>
○ Rain Garden (RR-6)	<input type="text"/> <input type="text"/> <input type="text"/>	. <input type="text"/> <input type="text"/> <input type="text"/>
○ Stormwater Planter (RR-7)	<input type="text"/> <input type="text"/> <input type="text"/>	. <input type="text"/> <input type="text"/> <input type="text"/>
○ Rain Barrel/Cistern (RR-8)	<input type="text"/> <input type="text"/> <input type="text"/>	. <input type="text"/> <input type="text"/> <input type="text"/>
○ Porous Pavement (RR-9)	<input type="text"/> <input type="text"/> <input type="text"/>	. <input type="text"/> <input type="text"/> <input type="text"/>
○ Green Roof (RR-10)	<input type="text"/> <input type="text"/> <input type="text"/>	. <input type="text"/> <input type="text"/> <input type="text"/>
Standard SMPs with RRv Capacity		
○ Infiltration Trench (I-1)	<input type="text"/> <input type="text"/> <input type="text"/>	. <input type="text"/> <input type="text"/> <input type="text"/>
○ Infiltration Basin (I-2)	<input type="text"/> <input type="text"/> <input type="text"/>	. <input type="text"/> <input type="text"/> <input type="text"/>
○ Dry Well (I-3)	<input type="text"/> <input type="text"/> <input type="text"/>	. <input type="text"/> <input type="text"/> <input type="text"/>
○ Underground Infiltration System (I-4)	<input type="text"/> <input type="text"/> <input type="text"/>	. <input type="text"/> <input type="text"/> <input type="text"/>
○ Bioretention (F-5)	<input type="text"/> <input type="text"/> <input type="text"/>	. <input type="text"/> <input type="text"/> <input type="text"/>
○ Dry Swale (O-1)	<input type="text"/> <input type="text"/> <input type="text"/>	. <input type="text"/> <input type="text"/> <input type="text"/>
Standard SMPs		
○ Micropool Extended Detention (P-1)	<input type="text"/> <input type="text"/> <input type="text"/>	. <input type="text"/> <input type="text"/> <input type="text"/>
○ Wet Pond (P-2)	<input type="text"/> <input type="text"/> <input type="text"/>	. <input type="text"/> <input type="text"/> <input type="text"/>
○ Wet Extended Detention (P-3)	<input type="text"/> <input type="text"/> <input type="text"/>	. <input type="text"/> <input type="text"/> <input type="text"/>
○ Multiple Pond System (P-4)	<input type="text"/> <input type="text"/> <input type="text"/>	. <input type="text"/> <input type="text"/> <input type="text"/>
○ Pocket Pond (P-5)	<input type="text"/> <input type="text"/> <input type="text"/>	. <input type="text"/> <input type="text"/> <input type="text"/>
○ Surface Sand Filter (F-1)	<input type="text"/> <input type="text"/> <input type="text"/>	. <input type="text"/> <input type="text"/> <input type="text"/>
○ Underground Sand Filter (F-2)	<input type="text"/> <input type="text"/> <input type="text"/>	. <input type="text"/> <input type="text"/> <input type="text"/>
○ Perimeter Sand Filter (F-3)	<input type="text"/> <input type="text"/> <input type="text"/>	. <input type="text"/> <input type="text"/> <input type="text"/>
○ Organic Filter (F-4)	<input type="text"/> <input type="text"/> <input type="text"/>	. <input type="text"/> <input type="text"/> <input type="text"/>
○ Shallow Wetland (W-1)	<input type="text"/> <input type="text"/> <input type="text"/>	. <input type="text"/> <input type="text"/> <input type="text"/>
○ Extended Detention Wetland (W-2)	<input type="text"/> <input type="text"/> <input type="text"/>	. <input type="text"/> <input type="text"/> <input type="text"/>
○ Pond/Wetland System (W-3)	<input type="text"/> <input type="text"/> <input type="text"/>	. <input type="text"/> <input type="text"/> <input type="text"/>
○ Pocket Wetland (W-4)	<input type="text"/> <input type="text"/> <input type="text"/>	. <input type="text"/> <input type="text"/> <input type="text"/>
○ Wet Swale (O-2)	<input type="text"/> <input type="text"/> <input type="text"/>	. <input type="text"/> <input type="text"/> <input type="text"/>

[illegible][illegible][illegible]

30. Indicate the Total RRv provided by the RR techniques (Area/Volume Reduction) and Standard SMPs with RRv capacity identified in question 29.

--	--	--

 ·

--	--	--

 acre-feet

- If Yes, go to question 36.
If No, go to question 32.

- | | | |
|--|--|--|
| | | |
|--|--|--|
-
- | | | |
|--|--|--|
| | | |
|--|--|--|
- acre-feet

- If No, sizing criteria has not been met, so NOI can not be processed. SWPPP preparer must modify design to meet sizing criteria.

33. Identify the Standard SMPs in Table 1 and, if applicable, the Alternative SMPs in Table 2 that were used to treat the remaining total WQv(=Total WQv Required in 28 - Total RRv Provided in 30).

Also, provide in Table 1 and 2 the total impervious area that contributes runoff to each practice selected.

Note: Use Tables 1 and 2 to identify the SMPs used on Redevelopment projects.

- 33a. Indicate the Total WQv provided (i.e. WQv treated) by the SMPs identified in question #33 and Standard SMPs with RRv Capacity identified in question 29.

WQv Provided

. acre-feet

Note: For the standard SMPs with RRv capacity, the WQv provided by each practice = the WQv calculated using the contributing drainage area to the practice - RRv provided by the practice. (See Table 3.5 in Design Manual)

34. Provide the sum of the Total RRv provided (#30) and the WQv provided (#33a).

.

35. Is the sum of the RRv provided (#30) and the WQv provided (#33a) greater than or equal to the total WQv required (#28)? ☐ Yes ☐ No

If Yes, go to question 36.

If No, sizing criteria has not been met, so NOI can not be processed. SWPPP preparer must modify design to meet sizing criteria.

36. Provide the total Channel Protection Storage Volume (CPv) required and provided or select waiver (36a), if applicable.

CPv Required

. acre-feet

CPv Provided

. acre-feet

- 36a. The need to provide channel protection has been waived because:

- ☐ Site discharges directly to tidal waters or a fifth order or larger stream.
- ☐ Reduction of the total CPv is achieved on site through runoff reduction techniques or infiltration systems.

37. Provide the Overbank Flood (Qp) and Extreme Flood (Qf) control criteria or select waiver (37a), if applicable.

Total Overbank Flood Control Criteria (Qp)

Pre-Development

. CFS

Post-development

. CFS

Total Extreme Flood Control Criteria (Qf)

Pre-Development

. CFS

Post-development

. CFS

37a. The need to meet the Qp and Qf criteria has been waived because:

- ☐ Site discharges directly to tidal waters or a fifth order or larger stream.
- ☐ Downstream analysis reveals that the Qp and Qf controls are not required

- Site discharges directly to tidal waters or a fifth order or larger stream.
- Downstream analysis reveals that the Qp and Qf controls are not required

☐ Yes ☐ No

If Yes, Identify the entity responsible for the long term
Operation and Maintenance

[illegible]

39. Use this space to summarize the specific site limitations and justification for not reducing 100% of WQv required(#28). (See question 32a)
This space can also be used for other pertinent project information.

40. Identify other DEC permits, existing and new, that are required for this project/facility.

○ Air Pollution Control

○ Coastal Erosion

☐ Hazardous Waste

○ Long Island Wells

○ Mined Land Reclamation

○ Solid Waste

○ Navigable Waters Protection / Article 15

○ Water Quality Certificate

○ Dam Safety

○ Water Supply

○ Freshwater Wetlands/Article 24

○ Tidal Wetlands

○ Wild, Scenic and Recreational Rivers

○ Stream Bed or Bank Protection / Article 15

○ Endangered or Threatened Species(Incidental Take Permit)

- Individual SPDES

○ SPDES Multi-Sector GP								
-------------------------	--	--	--	--	--	--	--	--

☐ Other _____

☐ None

41. Does this project require a US Army Corps of Engineers Wetland Permit? ☐ Yes ☐ No
If Yes, Indicate Size of Impact. Square Feet

42. Is this project subject to the requirements of a regulated, traditional land use control MS4? ☐ Yes ☐ No
(If No, skip question 43)

43. Has the "MS4 SWPPP Acceptance" form been signed by the principal executive officer or ranking elected official and submitted along with this NOI? ☐ Yes ☐ No

- [illegible]

Owner/Operator Certification	
<p>I have read or been advised of the permit conditions and believe that I understand them. I also understand that, under the terms of the permit, there may be reporting requirements. I hereby certify that this document and the corresponding documents were prepared under my direction or supervision. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations. I further understand that coverage under the general permit will be identified in the acknowledgment that I will receive as a result of submitting this NOI and can be as long as sixty (60) business days as provided in the general permit. I also understand that, by submitting this NOI, I am acknowledging that the SWPPP has been developed and will be implemented as the first element of construction, and agreeing to comply with all the terms and conditions of the general permit for which this NOI is being submitted.</p>	
Print First Name <div style="border: 1px solid black; height: 30px; width: 100%; position: relative;"> <div style="position: absolute; top: 0; left: 0; right: 0; bottom: 0; border: 1px solid black; display: flex; flex-wrap: wrap;"> <!-- 20 empty boxes for first name --> <!-- This is a simplified representation of the grid --> </div> </div>	MI <div style="border: 1px solid black; height: 30px; width: 100%; position: relative;"> <div style="position: absolute; top: 0; left: 0; right: 0; bottom: 0; border: 1px solid black; display: flex; flex-wrap: wrap;"> <!-- 2 empty boxes for MI --> </div> </div>
Print Last Name <div style="border: 1px solid black; height: 30px; width: 100%; position: relative;"> <div style="position: absolute; top: 0; left: 0; right: 0; bottom: 0; border: 1px solid black; display: flex; flex-wrap: wrap;"> <!-- 20 empty boxes for last name --> </div> </div>	
Owner/Operator Signature <div style="border: 1px solid black; height: 60px; width: 100%;"></div>	
<div style="display: flex; justify-content: flex-end; align-items: center;"> <div style="text-align: center; margin-right: 20px;"> Date <div style="border: 1px solid black; display: inline-block; width: 30px; height: 30px; line-height: 30px;"></div> <div style="border: 1px solid black; display: inline-block; width: 30px; height: 30px; line-height: 30px;"></div> <div style="font-size: 24px; margin: 0 5px;">/</div> <div style="border: 1px solid black; display: inline-block; width: 30px; height: 30px; line-height: 30px;"></div> <div style="border: 1px solid black; display: inline-block; width: 30px; height: 30px; line-height: 30px;"></div> <div style="border: 1px solid black; display: inline-block; width: 30px; height: 30px; line-height: 30px;"></div> </div> </div>	

APPENDIX E

CONSTRUCTION WASTE MANAGEMENT & SPILL PREVENTION PLAN

At the commencement of construction, land clearing materials will be collected and stored on-site for reuse. Construction debris such as cardboard, concrete, metal, wood and similar garbage will be collected in dumpsters and disposed of properly. An open top container will be on site during construction. The contractor will be responsible for organizing and placing containers on site and timely removal/replacement when containers are filled to capacity.

On-site storage of fuel chemicals shall be equipped with a spill kit. The contractor must provide secondary containment for storing any hazardous chemicals on site.

All equipment stored on site shall be inspected daily by the contractor for any oil or lubricant spills or leaks. Any leaks shall be repaired immediately. In addition, all equipment must be closely inspected prior to working in any R.O.W.

The contractor shall clean all spills immediately and shall report all spills to the New York State Department of Environmental Conservation.

This plan will be displayed in the construction jobsite trailer at all times.

APPENDIX F

Contractor Certification Statement

Site Plan & Subdivision
for 1251 Kings Highway

NYR _____

Name of Construction Site

DEC Permit ID

Municipality (MS4)

I hereby certify that I understand and agree to comply with the terms and conditions of the SWPPP and agree to implement any corrective actions identified by the *qualified inspector* during a site inspection. I also understand that the *owner or operator* must comply with the terms and conditions of the most current version New York State Pollution Discharge Elimination System ("SPDES") general permit for stormwater discharges from construction activities and that it is unlawful for any person to cause or contribute to a violation of water quality standards. Furthermore, I understand that certifying false, incorrect or inaccurate information is a violation of the referenced permit and the laws of State of New York and could subject me to criminal, civil and /or administrative proceedings.

Name _____

Title _____

Signature _____

Date _____

Company Name & Address _____

Phone _____

Project Site Address 1251 Kings Highway, Chester, NY

Provisions Responsible for _____

Information on the Trained Certified Contractor or Subcontractor

Name of Trained Employee

Title of Trained Employee

NYSDEC SWT#

A copy of this signed contractor certification statement must be maintained in the SWPPP on site.